

Technical Data Sheet

General

Article number: 9000xx

Description: Colad Orange™ Masking Tape



Specification

The Colad Orange™ Masking Tape is a high tack orange colored masking tape for masking jobs that provides a maximum job flexibility and that offers maximum performance in all types of conditions. This tape is Waterproof and UV resistant, easy removal without adhesive residue. Suitable for all types of paint systems! Now with improved tack and UV resistance!

Features:

- Color: Orange
- Adhesive type:
 - Natural rubber and resins solvent based, absolutely free of silicones.
 - High initial tack and good adhesion on all surfaces (metal and rubber).
- Highly resistant to moisture and water
- Removable without breaking
- Hand tear able
- Paper: Saturated Semi-Crepe Paper
- Thickness: 0.125 mm
- Weight: <70 g/m²
- Elongation: 8%
- Temperature resistance: 100°C for 1 hour
- UV resistant: 14 days outside
- Tensile strength MD: 360 N/100 mm width
- Adhesion to steel: 19.2 N/100 mm width
- Roll length: 50 m.

Product range overview:

Art.no.	Width x Length	Number of rolls per packing
900019	19 mm x 50 m	48 rolls
900025	25 mm x 50 m	36 rolls
900038	38 mm x 50 m	24 rolls
900050	50 mm x 50 m	24 rolls

Storage:

Store between 5-25 degrees, advised shelf life; 18 months.

Application:

When applied, the surface should be clean, dry and free of grease, oil and other contaminants.

Remarks

Engineered for the professional user, suitable in high demanding situations!

The Colad Orange™ Masking Tape is especially designed for professional use and is perfect where waterborne, 2K or UV curing systems are used.

Tape leaves no residue after removal, even after processing conditions up to 100 degrees for 1 hour.

Related products of Colad:

Article number : 9000

Description : UV Curing Light

Article number: 9150xx

Description: UV Putty Fine / Coarse

Article number: 9370xxxSLSUV

Description: Snap Lid System® UV

Article number: 2060xx + 2020

Description: Masking paper + Aprontaper

Disclaimer

It is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet via www.colad.co. It is the responsibility of the user to read and apply the information.

Notice

Products are for professional use. The repairs should always be done in accordance with the OEM rules and specifications. All information is for the user's consideration, investigation and verification.

The specific use applications and conditions of use are beyond the control of EMM International B.V. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

Created by

EMM International BV

Bohemestraat 19, 8028 SB Zwolle, The Netherlands

www.emm.com

T +31(0)38 467 66 00

www.colad.co