



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-8119-3
Revision date: 23/04/2025

Version number: 17.00
Supersedes date: 07/06/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 80349 Perfect-It III Extra Fine PLUS

Product Identification Numbers

GC-8010-4166-3 UU-0108-7968-0

7000084862 7100224682

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone: +353 1 280 3555
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008**

Not applicable

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH066

Repeated exposure may cause skin dryness or cracking.

EUH210

Safety data sheet available on request.

EUH208

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	50 - 70	Substance not classified as hazardous
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01-2119456620-43	15 - 40	Asp. Tox. 1, H304 EUH066
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	< 7	Substance with a national occupational exposure limit
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	1 - 5	Asp. Tox. 1, H304
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 920-107-4	1 - 5	Asp. Tox. 1, H304 EUH066
Undecan-1-ol, ethoxylated	(CAS-No.) 34398-01-1 (EC-No.) 500-084-3	< 0.3	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400,M=1 Aquatic Chronic 2, H411
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.005	Acute Tox. 2, H330(LC50 = 0.21 mg/l ATE values per Annex VI) Acute Tox. 4, H302(LD50 = 450 mg/kg ATE values per Annex VI) Skin Irrit. 2, H315 Eye Dam. 1, H318

			Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
--	--	--	---

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.036%) Skin Sens. 1A, H317
Undecan-1-ol, ethoxylated	(CAS-No.) 34398-01-1 (EC-No.) 500-084-3	(C >= 10%) Eye Dam. 1, H318 (5% <= C < 10%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Dermal defatting (localized redness, itching, drying and cracking of skin).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Condition

Carbon monoxide
Carbon dioxide.
Irritant vapours or gases.

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
Mineral oils, highly-refined oils	8042-47-5	Ireland OELs	TWA(inhalable fraction)(8 hours):5 mg/m ³	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur,

remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Solvent
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	> 125 °C [Test Method: Setaflash]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	8 - 8.5 Units not available or not applicable.
Kinematic Viscosity	30,303 - 40,404 mm ² /sec
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	0.917 g/cm ³ - 0.993 g/cm ³
Relative density	0.917 - 0.993 [Ref Std: WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds
 Evaporation rate
 Percent volatile

296.9 g/l
No data available.
 31 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

High shear and high temperature conditions

10.5 Incompatible materials

Alkali and alkaline earth metals.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	similar compounds	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	similar compounds	LD50 > 3,160 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	similar compounds	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	similar compounds	LD50 > 15,000 mg/kg
Undecan-1-ol, ethoxylated	Dermal	Rabbit	LD50 > 2,000 mg/kg
Undecan-1-ol, ethoxylated	Ingestion	Rat	LD50 > 700 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.21 mg/l
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 450 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar compounds	Mild irritant
Undecan-1-ol, ethoxylated	similar health hazards	Irritant
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar compounds	No significant irritation
Undecan-1-ol, ethoxylated	Professional judgement	Corrosive
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar compounds	Not classified
1,2-benzisothiazol-3(2H)-one	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation

1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation
------------------------------	-----------	--------------------------------	-----	---------------------	--------------

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Undecan-1-ol, ethoxylated	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
1,2-benzisothiazol-3(2H)-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	hematopoietic system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	kidney and/or	Not classified	Rat	LOAEL 100	13 weeks

n-alkanes, isoalkanes, cyclics, < 2% aromatics		bladder			mg/kg/day	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	hematopoietic system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
1,2-benzisothiazol-3(2H)-one	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)-one	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l

Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Estimated	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Undecan-1-ol, ethoxylated	34398-01-1	Green algae	Analogous Compound	72 hours	ErC50	0.43 mg/l
Undecan-1-ol, ethoxylated	34398-01-1	Green algae	Analogous Compound	72 hours	NOEC	0.09 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	ErC50	0.11 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Sheepshead Minnow	Experimental	96 hours	LC50	16.7 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Activated sludge	Experimental	3 hours	EC50	12.8 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight
1,2-benzisothiazol-3(2H)-one	2634-33-5	Cabbage	Experimental	14 days	EC50	200 mg/kg (Dry Weight)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Redworm	Experimental	14 days	LC50	>410.6 mg/kg (Dry Weight)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Soil microbes	Experimental	28 days	EC50	>811.5 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 %BOD/ThO D	OECD 301F - Manometric respirometry
Aluminium oxide	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Experimental Biodegradation	28 days	BOD	69 %BOD/ThO D	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Estimated Biodegradation	28 days	BOD	67.6 %BOD/ThO D	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Undecan-1-ol, ethoxylated	34398-01-1	Modeled Biodegradation	28 days	CO2 evolution	95 %CO2 evolution/THC O2 evolution	Catalogic™
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 %BOD/ThO D	OECD 301C - MITI test (I)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Aquatic Inherent Biodegrad.	34 days	Dissolv. Organic Carbon Deplet	17 %removal of DOC	OECD 302A - Modified SCAS Test
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	80 %removal of DOC	OECD 303A - Simulated Aerobic
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation		Half-life (t 1/2)	4 hours (t 1/2)	
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Hydrolysis		Hydrolytic half-life	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Undecan-1-ol, ethoxylated	34398-01-1	Modeled Bioconcentration		Bioaccumulation factor	50	Catalogic™
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental BCF - Fish	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Undecan-1-ol, ethoxylated	34398-01-1	Estimated Mobility in Soil	Koc	2,472 l/kg	
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Mobility in Soil	Koc	9.33 l/kg	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.

14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained

substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Contains statement for sensitizers information was added.

List of sensitizers information was added.

Section 3: Composition/ Information of ingredients table information was modified.

Section 03: SCL table information was modified.

Section 04: First Aid - Symptoms and Effects (CLP) information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 08: Skin protection - incidental contact text information was added.

Section 08: Skin protection - incidental contact information was added.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Particle Characteristics N/A information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Annex

1. Title

Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6; Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 920-107-4;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Processes, tasks and activities covered	Application of product with microfiber towel, cloth, or brush
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: Daily; Emission days per year: 300 days/year; Frequency of exposure at workplace [for one worker]: 8 hours/day; Indoor use; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Processes, tasks and activities covered	Application of product.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management

	measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com