



GREY STRIPE

DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

Version: 1.0

Brushable Seam Sealer

TECHNICAL DATA SHEET & PROCESS GUIDE

GREYSTRIPE is a flexible brushable seam sealer for the overcoating of weld seams in luggage and engine compartments.

GREYSTRIPE can be over-painted with most paint systems.

PROPERTIES

- Ready to use 1K formula
- High build formula covers weld marks and seams
- Protects against stone chips, salt, damp and rust

Available Colours • Grey

TECHNICAL DATA



Substrates

- Original Paint
- Bare steel

APPLICATION GUIDE



Tools Required

- Degreaser
- Brush
- Abrasives
- Painters Overalls



Substrate Preparation

To achieve best results, good preparation is essential. Degrease with U-POL Precleaner (S2000, S2001 or S2002). :

remove loose debris and grease

Apply generously and evenly with a brush, always brushing along the seam. One coat is adequate for most applications



Drying Times

Drying time @ 20°C

6 - 10 mins for surface dry depending on film build and ambient temperature

Through dry in 7 - 8 hours depending on film build and ambient temperature



Over Painting

GREY STRIPE can be overpainted with most paint systems.



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

Version: 1.0

GREY STRIPE

Brushable Seam Sealer

TECHNICAL DATA SHEET & PROCESS GUIDE STORAGE & VOC INFORMATION



Shelf Life

2 years from date of manufacture in sealed original containers.

Recommended Storage Temperature 5°C - 25°C

Equipment Cleaning Equipment can be cleaned with standard solvent based thinner.

VOC Information



The EU limit for this product (product category: IIbE) in ready to use form is 840g/litre.

The VOC content of this product in ready to use form is 535g/litre

Order Code	Format	Colour
GS/1	1L tin	GREY

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL Ltd

4th Floor, The Grange, 100 High Street
London, N14 6BN
WWW.U-POL.COM

UK Sales

T: +44 (0)20 8492 5920
F: +44 (0)20 8150 5605
uk.sales@u-pol.com

International

T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical

T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com