



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|----------------|
| Document group: | 31-0232-4 | Version number: | 1.00 |
| Revision date: | 05/03/2021 | Supersedes date: | Initial issue. |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

Product Identification Numbers

DE-2729-6627-1 DE-2729-6632-1

7000062763 7000062768

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

EU Member State Responsible Contact

Address: 3M Ireland Ltd, The Iveagh Building, Carrickmines Park, Dublin D18 X015.
Telephone: +353 1 280 3555

1.4. Emergency telephone number

+44 (0)1344 858 000 or call your doctor.

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Organic Peroxide, Type E - Org. Perox. E; H242

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1B - Skin Sens. 1B; H317

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|--------------------|---------|-----------|---------|
| dibenzoyl peroxide | 94-36-0 | 202-327-6 | 45 - 55 |

HAZARD STATEMENTS:

| | |
|------|---|
| H242 | Heating may cause a fire. |
| H319 | Causes serious eye irritation. |
| H317 | May cause an allergic skin reaction. |
| H410 | Very toxic to aquatic life with long lasting effects. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P234 | Keep only in original packaging. |
| P273 | Avoid release to the environment. |
| P280B | Wear protective gloves and eye/face protection. |

Response:

| | |
|--------------------|--|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P370 + P378 | In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish. |

Storage:

| | |
|------|--|
| P403 | Store in a well-ventilated place. |
| P411 | Store at temperatures not exceeding 25C/77F. |

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280B Wear protective gloves and eye/face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Ingredient | Identifier(s) | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---------------------------|--|---------|--|
| dibenzoyl peroxide | (CAS-No.) 94-36-0 (EC-No.) 202-327-6 | 45 - 55 | Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10 |
| Dimethyl phthalate | (CAS-No.) 131-11-3 (EC-No.) 205-011-6 | 25 - 35 | Substance with a national occupational exposure limit |
| Non-Hazardous Ingredients | Mixture | 15 - 25 | Substance not classified as hazardous |
| ethanediol | (CAS-No.) 107-21-1 (EC-No.) 203-473-3 | < 10 | Acute Tox. 4, H302 STOT RE 2, H373 |

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product. Part of the oxygen for combustion is supplied by the peroxide itself.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|-------------------------|-------------------------|
| Carbon monoxide | During combustion. |
| Carbon dioxide. | During combustion. |
| Toxic Vapour/Gas | During combustion. |

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store at temperatures not exceeding 25C/77F. Keep cool. Keep only in original container. Store away from acids. Store away from other materials. Keep/store away from clothing and other combustible materials. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|--------------------|----------------|---------------|--|----------------------------|
| ethanediol | 107-21-1 | UK HSC | TWA(as vapor):52 mg/m3(20 ppm);TWA(as particulate):10 mg/m3;STEL(as vapor):104 mg/m3(40 ppm) | SKIN |
| Dimethyl phthalate | 131-11-3 | UK HSC | TWA:5 mg/m3;STEL:10 mg/m3 | |
| dibenzoyl peroxide | 94-36-0 | UK HSC | TWA:5 mg/m3 | |

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|------------------|-----------------------|--------------------------|
| Polymer laminate | >.3 | > 8 hours |

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|-------------------------------------|----------------------|
| Physical state | Liquid. |
| Specific Physical Form: | Paste |
| Colour | Red |
| Odor | Characteristic Odour |
| Odour threshold | No data available. |
| Melting point/freezing point | No data available. |
| Boiling point/boiling range | No data available. |
| Flammability (solid, gas) | Not applicable. |
| Flammable Limits(LEL) | No data available. |
| Flammable Limits(UEL) | No data available. |

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

| | |
|--|---|
| Flash point | No data available. |
| Autoignition temperature | Not applicable. |
| Decomposition temperature | 50 °C [Details:SADT] |
| pH | substance/mixture is non-soluble (in water) |
| Kinematic Viscosity | No data available. |
| Water solubility | Nil |
| Solubility- non-water | No data available. |
| Partition coefficient: n-octanol/water | No data available. |
| Vapour pressure | 100 Pa [@ 20 °C] |
| Density | 1.1 g/ml |
| Relative density | 1.1 [Ref Std:WATER=1] |
| Relative Vapor Density | No data available. |

9.2. Other information

9.2.2 Other safety characteristics

| | |
|-------------------------------|--------------------|
| EU Volatile Organic Compounds | 109 g/l |
| Evaporation rate | No data available. |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable. Unstable at or above 50 deg C. (Self-accelerating decomposition temperature)

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.
Temperatures above +25°C

10.5 Incompatible materials

Accelerators
Alkali and alkaline earth metals.
Amines.
Reducing agents.
Strong acids.
Combustibles.

10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from

internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

May be harmful in contact with skin. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------|--------------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| dibenzoyl peroxide | Dermal | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| dibenzoyl peroxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 24.3 mg/l |
| dibenzoyl peroxide | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Dimethyl phthalate | Inhalation-Dust/Mist (4 hours) | Other | LC50 > 15.1 mg/l |
| Dimethyl phthalate | Dermal | Rabbit | LD50 > 11,940 mg/kg |
| Dimethyl phthalate | Ingestion | Rat | LD50 6,800 mg/kg |
| ethanediol | Ingestion | Human | LD50 1,600 mg/kg |
| ethanediol | Inhalation-Dust/Mist (4 hours) | Other | LC50 estimated to be 5 - 12.5 mg/l |
| ethanediol | Dermal | Rabbit | 9,530 mg/kg |

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--------------------|---------|--------------------|
| dibenzoyl peroxide | Rabbit | Minimal irritation |
| ethanediol | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--------------------|---------|-----------------|
| dibenzoyl peroxide | Rabbit | Severe irritant |
| ethanediol | Rabbit | Mild irritant |

Skin Sensitisation

| Name | Species | Value |
|--------------------|------------|----------------|
| dibenzoyl peroxide | Guinea pig | Sensitising |
| ethanediol | Human | Not classified |

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------|----------|---------------|
| dibenzoyl peroxide | In Vitro | Not mutagenic |
| dibenzoyl peroxide | In vivo | Not mutagenic |
| ethanediol | In Vitro | Not mutagenic |
| ethanediol | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------|-----------|-------------------------|--|
| dibenzoyl peroxide | Ingestion | Multiple animal species | Not carcinogenic |
| dibenzoyl peroxide | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| ethanediol | Ingestion | Multiple animal species | Not carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|--------------------|-----------|--|---------|-----------------------|------------------------------|
| dibenzoyl peroxide | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |
| dibenzoyl peroxide | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | premating & during gestation |
| dibenzoyl peroxide | Ingestion | Not classified for development | Rat | NOAEL 500 mg/kg/day | premating & during gestation |
| ethanediol | Dermal | Not classified for development | Mouse | NOAEL 3,549 mg/kg/day | during organogenesis |
| ethanediol | Ingestion | Not classified for development | Mouse | LOAEL 750 | during |

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

| | | | | | |
|------------|------------|--------------------------------|-------|-----------------------------|-------------------------|
| | | | | mg/kg/day | organogenesis |
| ethanediol | Inhalation | Not classified for development | Mouse | NOAEL 1,000 mg/kg/day | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------|-----------|---|-----------------------------------|---------|---------------------|------------------------|
| ethanediol | Ingestion | heart nervous system kidney and/or bladder respiratory system | Causes damage to organs | Human | NOAEL Not available | poisoning and/or abuse |
| ethanediol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| ethanediol | Ingestion | liver | Not classified | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------|-----------|---|--|-------------------------|------------------------|-------------------|
| ethanediol | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 200 mg/kg/day | 2 years |
| ethanediol | Ingestion | vascular system | Not classified | Rat | NOAEL 200 mg/kg/day | 2 years |
| ethanediol | Ingestion | heart hematopoietic system liver immune system muscles | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| ethanediol | Ingestion | respiratory system | Not classified | Mouse | NOAEL 12,000 mg/kg/day | 2 years |
| ethanediol | Ingestion | skin endocrine system bone, teeth, nails, and/or hair nervous system eyes | Not classified | Multiple animal species | NOAEL 1,000 mg/kg/day | 2 years |

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|--------------------|----------|-------------------|--------------|------------|---------------|-------------|
| dibenzoyl peroxide | 94-36-0 | Activated sludge | Experimental | 30 minutes | EC50 | 35 mg/l |
| dibenzoyl peroxide | 94-36-0 | Green Algae | Experimental | 72 hours | EC50 | 0.071 mg/l |
| dibenzoyl peroxide | 94-36-0 | Rainbow trout | Experimental | 96 hours | LC50 | 0.06 mg/l |
| dibenzoyl peroxide | 94-36-0 | Water flea | Experimental | 48 hours | EC50 | 0.11 mg/l |
| dibenzoyl peroxide | 94-36-0 | Green Algae | Experimental | 72 hours | NOEC | 0.02 mg/l |
| dibenzoyl peroxide | 94-36-0 | Water flea | Experimental | 21 hours | EC10 | 0.001 mg/l |
| Dimethyl phthalate | 131-11-3 | Activated sludge | Experimental | 30 minutes | EC20 | 400 mg/l |
| Dimethyl phthalate | 131-11-3 | Green algae | Experimental | 72 hours | EC50 | 260 mg/l |
| Dimethyl phthalate | 131-11-3 | Sheepshead Minnow | Experimental | 96 hours | LC50 | 29 mg/l |
| Dimethyl phthalate | 131-11-3 | Water flea | Experimental | 48 hours | LC50 | 33 mg/l |
| Dimethyl phthalate | 131-11-3 | Green algae | Experimental | 72 hours | EC10 | 193 mg/l |
| Dimethyl phthalate | 131-11-3 | Rainbow trout | Experimental | 102 days | NOEC | 11 mg/l |
| Dimethyl phthalate | 131-11-3 | Water flea | Experimental | 21 days | NOEC | 9.6 mg/l |
| ethanediol | 107-21-1 | Bacteria | Experimental | 16 hours | EC50 | 10,000 mg/l |
| ethanediol | 107-21-1 | Fathead minnow | Experimental | 96 hours | LC50 | 8,050 mg/l |
| ethanediol | 107-21-1 | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| ethanediol | 107-21-1 | Water flea | Experimental | 48 hours | EC50 | >1,100 mg/l |
| ethanediol | 107-21-1 | Green Algae | Experimental | 72 hours | NOEC | 1,000 mg/l |
| ethanediol | 107-21-1 | Water flea | Experimental | 21 days | NOEC | 100 mg/l |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|--------------------|----------|-----------------------------|----------|--------------------------------|-------------------|--------------------------------|
| dibenzoyl peroxide | 94-36-0 | Experimental Hydrolysis | | Hydrolytic half-life | <24 hours (t 1/2) | Non-standard method |
| dibenzoyl peroxide | 94-36-0 | Experimental Biodegradation | 28 days | BOD | 71 % weight | OECD 301D - Closed bottle test |
| Dimethyl phthalate | 131-11-3 | Experimental Biodegradation | 11 days | Dissolv. Organic Carbon Deplet | 91 % weight | OECD 301E - Modif. OECD Screen |
| ethanediol | 107-21-1 | Experimental Biodegradation | 14 days | BOD | 90 % BOD/ThBOD | OECD 301C - MITI test (I) |

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|--------------------|----------|-------------------------------|----------|------------------------|-------------|---------------------|
| dibenzoyl peroxide | 94-36-0 | Experimental Bioconcentration | | Log Kow | 3.2 | Non-standard method |
| Dimethyl phthalate | 131-11-3 | Experimental BCF - Bluegill | 21 days | Bioaccumulation factor | 57 | Non-standard method |
| ethanediol | 107-21-1 | Experimental Bioconcentration | | Log Kow | -1.36 | Non-standard method |

12.4. Mobility in soil

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

| | Ground Transport (ADR) | Air Transport (IATA) | Marine Transport (IMDG) |
|--|---|---|---|
| 14.1 UN number | UN3108 | UN3108 | UN3108 |
| 14.2 UN proper shipping name | ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%) | ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%) | ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%) |
| 14.3 Transport hazard class(es) | 5.2 | 5.2 | 5.2 |
| 14.4 Packing group | Not applicable. | Not Applicable | Not Applicable |

3M™Body filler Red Hardener 51074, 51077, 51080, 51084

| | | | |
|--|--|--|--|
| 14.5 Environmental hazards | Not Environmentally Hazardous | Not applicable | Not a Marine Pollutant |
| 14.6 Special precautions for user | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. |
| 14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code | No data available. | No Data Available | No Data Available |
| Control Temperature | No data available. | No Data Available | No Data Available |
| Emergency Temperature | No data available. | No Data Available | No Data Available |
| ADR Tunnel Code | (E) | Not Applicable | Not Applicable |
| ADR Classification Code | P1 | Not Applicable | Not Applicable |
| ADR Transport Category | 2 | Not Applicable | Not Applicable |
| ADR Multiplier | 0 | 0 | 0 |
| IMDG Segregation Code | Not applicable. | Not Applicable | NONE |
| Transport not Permitted | Not applicable. | Not Applicable | Not Applicable |

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient**

dibenzoyl peroxide

CAS Nbr

94-36-0

Classification

Gr. 3: Not classifiable

RegulationInternational Agency
for Research on Cancer**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

| | |
|------|--|
| H241 | Heating may cause a fire or explosion. |
| H242 | Heating may cause a fire. |
| H302 | Harmful if swallowed. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk