

### **SAFETY DATA SHEET**

ISOPON BODYFILLER RANGE

Page 1

Issued: 17/08/2004

Revision No: 1

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ISOPON BODYFILLER RANGE

Product code: VARIOUS

Synonyms: P38, P40, BUMPERFILL, JUNIOR, METALIK

Use / description of product: POLYESTER REPAIR PASTE CONTAINING STYRENE

Company name: U-Pol Products

**Denington Industrial Estate** 

Denington Road Wellingborough

Northants NN8 2QP

United Kingdom

Tel: 44-(0)-1933 230300 Fax: 44-(0)-1933 230351

Emergency tel: 44-(0)-1933 230310

# 2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: STYRENE 10-30%

EINECS: 202-851-5 CAS: 100-42-5 [-] R10; [Xn] R20; [Xi] R36/38

### 3. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes and skin.

Other hazards: Flammable. Harmful by inhalation. Irritating to eyes. Irritating to skin.

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

### 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

#### Issued: 17/08/2004

### **SAFETY DATA SHEET**

ISOPON BODYFILLER RANGE

Page 2

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

### 5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

**Exposure hazards:** Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand.

#### 7. HANDLING AND STORAGE

**Handling requirements:** Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly

closed.

Suitable packaging: Must only be kept in original packaging.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: STYRENE

TWA (8 hr exposure limit): 430 mg/m3 STEL (15 min exposure limit): 1080 mg/m3 (MEL)

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protective device with particle filter.

Hand protection: Nitrile gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Odour: Aromatic

**Evaporation rate:** Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Viscosity value: 500,000 CP

Flammability limits %: lower: 1.1

upper: 6.1

Flash point°C: 32

Autoflammability°C: 490

Relative density: 1.5

VOC g/I: 300

#### Issued: 17/08/2004

### **SAFETY DATA SHEET**

ISOPON BODYFILLER RANGE

Page 3

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

Materials to avoid: Oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### 11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: STYRENE

IVN MUS LD50 90 mg/kg
ORL MUS LD50 316 mg/kg
ORL RAT LD50 2650 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water. Heavier than water.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: Toxic to aquatic organisms.

### 13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

# 14. TRANSPORT INFORMATION

#### ADR / RID

**UN no**: 3269 **ADR Class**: 3

Packing group: III Classification code: F1

Shipping name: POLYESTER RESIN KIT

Labelling: 3



# **IMDG / IMO**

**UN no**: 3269 **Class**: 3

Packing group: ||| EmS: F-E,S-D

Marine pollutant: . Labelling: 3

#### Issued: 17/08/2004

### **SAFETY DATA SHEET**

ISOPON BODYFILLER RANGE

Page 4

IATA / ICAO

UN no: 3269 Class: 3

Packing group: ||| Packing instructions: 312

Labelling: 3

### 15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

Safety phrases: S2: Keep out of the reach of children.

S3: Keep in a cool place.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

VbF: All

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

# **16. OTHER INFORMATION**

Risk phrases used in s.2: R10: Flammable.

R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.