3hp

100L

13.4 cfm





with Cast Cylinders Model No. SEE TABLE

Suitable for the professional workshop, these units are fitted with a genuine 3hp motor. Twin capacitors and a centrifugal switch aid trouble-free start-up on a 13A supply. Pumps feature heavy-duty full cast cylinders, capped by alloy heads for improved heat dissipation and long-life. Heavy-duty drive guards protect belt and flywheel that is designed to force air over the pump to aid cooling.



All models on this page feature full cast iron cylinders.



E Fully Synthetic Compressor Oil Model No. SEE BELOW

Top grade fully synthetic oil suitable for Sealey and other leading brands of compressor. Supplied in 1 litre and 5 litre containers. Ideal for Belt Drive Compressors especially to aid start-up in cold conditions.

Model No:	Size:	Pack Qty:
FSO1S	1L	1
FSO5	5L	1





	A	В	C	D
Model No:	SAC1503B	SAC1103B	SAC1153B	SAC1203B
Motor Output:	3hp	3hp	3hp	3hp
Supply:	230V	230V	230V	230V
Phase:	1ph	1ph	1ph	1ph
Minimum Rated Supply:	13A	13A	13A	13A
Speed:	1630rpm	1630rpm	1630rpm	1630rpm
Air Displacement cfm(L/min):	13.4(380)	13.4(380)	13.4(380)	13.4(380)
Maximum Free Air Delivery cfm(L/min):	8.8(249)	8.8(249)	8.8(249)	8.8(249)
Maximum Pressure:	145psi(10bar)	145psi(10bar)	145psi(10bar)	145psi(10bar)
Receiver Capacity:	50L	100L	150L	200L
Outlet:	Quick Release Coupling	Quick Release Coupling	1/2"BSP Female Tap	1/2"BSP Female Tap
Size (W x D x H):	1020 x 390 x 740mm	1010 x 470 x 860mm	1320 x 400 x 820mm	1440 x 440 x 865mm
Weight:	50kg	59kg	78kg	90kg