prevost
Compressed Air Expert

STOFLEX HOSE ASSEMBLIES ANTI-STATIC RUBBER PAINTING

STOFLEX anti-static rubber hose extension with PREVOS1 safety quick couplers

Profile : ISO 6150B



Max. operating pressure	Min. / Max temperature
12 bar	-15 / 70 °C

Part number	Length (m)	Ø int/ext (mm)	Profile	For pipe ID	ID passage	Net weight (Kg)
RAL SISB810	10	8 / 15	ISO 6150B	8	6 mm	1.960
RAL SISB1012	12.5	10 / 18	ISO 6150B	10	6 mm	2.850
RAL SESB810	10	8 / 15	EUROPEAN	8	7.4 mm	1.820
RAL SESB1012	12.5	10 / 18	EUROPEAN	10	7.4 mm	3.080
RAL SBSB810	10	8 / 15	BRITISH	8	6 mm	1.900
RAL SBSB1012	12.5	10 / 18	BRITISH	10	6 mm	3.100
RAL SCSB810	10	8 / 15	ISO 6150C	8	6 mm	1.900
RAL SCSB1012	12.5	10 / 18	ISO 6150C	10	6 mm	2.500
RAL SASB810	10	8 / 15	ARO 210	8	6 mm	2.300
RAL SASB1012	12.5	10 / 18	ARO 210	10	6 mm	3.240

Fitted with ear clamps and protectors

Prevost UK Ltd - Unit G, Tower Business Park - Commercial Road - Darwen - BB3 OFJ - UK
Tel. +44 (0)125 487 3389 - salesupport.uk@prevost.eu - www.prevost.eu