

Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 27-0547-3
 Version number:
 7.02

 Revision date:
 26/06/2018
 Supersedes date:
 14/02/2018

Transportation version number: 24.00 (06/04/2020)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M 50873 Colour Coded Polishing Kit

Product Identification Numbers

UU-0030-2866-7

7100058122

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

19-1306-0, 22-4541-3, 27-4388-8, 27-8119-3

TRANSPORTATION INFORMATION

UU-0030-2866-7

Not hazardous for transportation

KIT LABEL

2.1. Classification of the substance or mixture

.....

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336 Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Contains:

Naphtha (petroleum), hydrotreated heavy; Naphtha (petroleum), hydrodesulfurised heavy

HAZARD STATEMENTS:

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure:

nervous system |

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260E Do not breathe vapour or spray.
P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

EUH208 Contains 1,2-Benzisothiazol-3(2H)-one.May produce an allergic reaction.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Notes on labelling

H304 is not required on the label due to the product's viscosity Nota P applied to CASRNs 64742-82-1 and 64742-48-9.

3M 50873 Colour Coded Polishing Kit

Nota L applied to CASRN 64741-88-4.

Revision information:

Label: CLP Ingredients - kit components information was added.



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 22-4541-3
 Version number:
 21.03

 Revision date:
 25/08/2021
 Supersedes date:
 07/07/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Perfect-It III Fast Cut Plus Compound 50417 and 51299

Product Identification Numbers

GC-8010-2249-9 GC-8010-2861-1 GC-8010-2862-9 UU-0108-7967-2

7000084531 7000084366 7000034386 7100221414

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 E Mail: tox.uk@mmm.com Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

3M Perfect-It III Fast Cut Plus Compound 50417 and 51299

CLASSIFICATION:

Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient CAS Nbr EC No. % by Wt

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, 919-446-0 10 - 15 aromatics (2-25%)

HAZARD STATEMENTS:

H372 Causes damage to organs through prolonged or repeated exposure: nervous system.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260A Do not breathe vapours.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Non-Hazardous Ingredients	Mixture	30 - 60	Substance not classified as hazardous
Aluminium Oxide (non-fibrous)	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6 (REACH-No.) 01- 2119529248-35	10 - 30	Substance with a national occupational exposure limit
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC-No.) 919-446-0	10 - 15	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 STOT RE 1, H372
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01- 2119456620-43	7 - 13	Asp. Tox. 1, H304 EUH066
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	1 - 5	Asp. Tox. 1, H304
Glycerin	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	1 - 5	Substance with a national occupational exposure limit
Sorbitan monooleate, ethoxylated	Trade Secret	1 - 5	Substance not classified as hazardous
Hydrocarbons, C10 aromatics, <1% naphthalene	(EC-No.) 918-811-1 (REACH-No.) 01- 2119463583-34	1 - 4	Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 Aquatic Chronic 2, H411
Castor oil	(CAS-No.) 8001-79-4 (EC-No.) 232-293-8	1 - 3	Substance not classified as hazardous
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400,M=10

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.05%) Skin Sens. 1, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include: Toxic by eye contact. Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionHydrocarbons.During combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep cool. Store away from heat. Store away from acids. Store away from oxidising agents. Store away from areas where product may come into contact with food or pharmaceuticals.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSC	TWA(as respirable dust):4	
			mg/m3;TWA(as inhalable	
			dust):10 mg/m3	
Glycerin	56-81-5	UK HSC	TWA(as mist):10 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material Thickness (mm) Breakthrough Time

Polymer laminate >0.30 4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:SlurryColourWhiteOdorParaffinic

Odour thresholdNo data available.Melting point/freezing pointNot applicable.Boiling point/boiling range> 65 °CFlammability (solid, gas)Not applicable.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.

Flash point >=65 °C [Test Method:Pensky-Martens Closed Cup]

3M Perfect-It III Fast Cut Plus Compound 50417 and 51299

Autoignition temperatureNo data available.Decomposition temperatureNo data available.

pH 7.5 - 9

Kinematic Viscosity 26,086.9565217391 mm²/sec

Water solubilityNo data available.Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNo data available.

Density 1.15 g/ml

Relative density 1.15 [Ref Std: WATER=1]

Relative Vapor Density *No data available.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rateNot applicable.

Percent volatile

25.5 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

High shear and high temperature conditions Sparks and/or flames.

10.5 Incompatible materials

Alkali and alkaline earth metals. Strong oxidising agents.

10.6 Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause target organ effects after inhalation. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation. Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal	•	No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation- Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%	Ingestion	Rat	LD50 > 5,000 mg/kg
aromatics			
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Dermal	Not	LD50 > 5,000 mg/kg
		available	
Sorbitan monooleate, ethoxylated	Inhalation-	Rat	LC50 > 5.1 mg/l
	Dust/Mist		
	(4 hours)		
Sorbitan monooleate, ethoxylated	Ingestion	Rat	LD50 20,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation-	Professio	LC50 estimated to be 20 - 50 mg/l
	Vapour	nal	
		judgeme	
		nt	
Hydrocarbons, C10 aromatics, <1% naphthalene	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Castor oil	Dermal		LD50 estimated to be > 5,000
Castor oil	Ingestion		LD50 estimated to be > 5,000
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 454 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name		Value
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	Minimal irritation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Minimal irritation
Glycerin	Rabbit	No significant irritation
Castor oil	Human	Minimal irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name Species Value					
Trume	Species	, and			
	70 1111	NY 1 100 11 11 11			
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	No significant irritation			
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant			
White mineral oil (petroleum)	Rabbit	Mild irritant			
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation			
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Mild irritant			
Glycerin	Rabbit	No significant irritation			
Castor oil	Rabbit	Mild irritant			
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive			

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Guinea	Not classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Sorbitan monooleate, ethoxylated	Guinea pig	Not classified
Hydrocarbons, C10 aromatics, <1% naphthalene	Guinea	Not classified

	pig	
Glycerin	Guinea	Not classified
	pig	
Castor oil	Human	Not classified
1,2-benzisothiazol-3(2H)-one	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value		
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic		
White mineral oil (petroleum)	In Vitro	Not mutagenic		
Sorbitan monooleate, ethoxylated	In Vitro	Not mutagenic		
Hydrocarbons, C10 aromatics, <1% naphthalene	In Vitro	Not mutagenic		
Hydrocarbons, C10 aromatics, <1% naphthalene	In vivo	Not mutagenic		
Castor oil	In Vitro	Not mutagenic		
Castor oil	In vivo	Not mutagenic		
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic		
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not		
		sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not available	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Sorbitan monooleate, ethoxylated	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL	3 generation

Page 10 of 1

				6,666 mg/kg/day	
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2-benzisothiazol-3(2H)- one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, eyclics, aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Sorbitan monooleate, ethoxylated	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails,	Not classified	Rat	NOAEL 4,132 mg/kg/day	90 days

		and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system				
Glycerin	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Castor oil	Ingestion	heart hematopoietic system liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Castor oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
1,2-benzisothiazol-3(2H)- one	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Aspiration hazard
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C10 aromatics, <1% naphthalene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l

Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2- 25%)	919-446-0	Green algae	Estimated	72 hours	EL50	4.1 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2- 25%)	919-446-0	Rainbow trout	Estimated	96 hours	LL50	10 - 30 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2- 25%)	919-446-0	Water flea	Estimated	48 hours	EL50	10 - 22 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2- 25%)	919-446-0	Green algae	Estimated	72 hours	NOEL	0.76 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2- 25%)	919-446-0	Water flea	Estimated	21 days	EC10	0.316 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l
Glycerin	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Sorbitan monooleate, ethoxylated	Trade Secret	Copepods	Estimated	48 hours	LL50	>10,000 mg/l
Sorbitan monooleate, ethoxylated	Trade Secret	Green Algae	Estimated	72 hours	EL50	58.84 mg/l
Sorbitan monooleate, ethoxylated	Trade Secret	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Sorbitan monooleate, ethoxylated	Trade Secret	Green Algae	Estimated	72 hours	EC10	19.05 mg/l
Sorbitan monooleate, ethoxylated	Trade Secret	Water flea	Estimated	21 days	NOEL	10 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	NOEL	>100 mg/l
Hydrocarbons, C10 aromatics, <1%	918-811-1	Green Algae	Estimated	72 hours	EL50	3 mg/l
naphthalene	I	<u> </u>		l		

Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Rainbow trout	Estimated	96 hours	LL50	5 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Water flea	Estimated	48 hours	EL50	10 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Green Algae	Estimated	72 hours	NOEL	1 mg/l
Castor oil	8001-79-4	Bacteria	Estimated	16 hours	NOEC	10,000 mg/l
Castor oil	8001-79-4	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	EC50	0.11 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Pacific oyster	Experimental	48 hours	EC50	0.062 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non- fibrous)	1344-28-1	Data not availbl- insufficient			N/A	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Estimated Biodegradation	28 days	BOD	75 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % BOD/ThBOD	OECD 301C - MITI test (I)
Sorbitan monooleate, ethoxylated	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	61 % weight	Non-standard method
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Experimental Biodegradation	28 days	BOD	49.6 %BOD/C OD	OECD 301F - Manometric respirometry
Castor oil	8001-79-4	Estimated Biodegradation	28 days	BOD	64 % weight	OECD 301D - Closed bottle test
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, eyclics, aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Non-standard method
Sorbitan monooleate,	Trade Secret	Data not available	N/A	N/A	N/A	N/A

ethoxylated		or insufficient for classification				
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Castor oil	8001-79-4	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental BCF - Bluegill	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Glycerin	56-81-5	Estimated Mobility in Soil	Koc	<1 l/kg	Episuite TM
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental Mobility in Soil		ERROR: Length cannot be greater than the length of the string.	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG) No data available.		
14.1 UN number	No data available.	No data available.			
14.2 UN proper shipping name	No data available.	No data available.	No data available.		
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.		
14.4 Packing group	No data available.	No data available.	No data available.		
14.5 Environmental hazards	No data available.	No data available.	No data available.		
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.		
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.		
Control Temperature	No data available.	No data available.	No data available.		
Emergency Temperature	No data available.	No data available.	No data available.		
ADR Tunnel Code	No data available.	Not applicable.	No data available.		
ADR Classification Code	ADR Classification Code No data available.		No data available.		
ADR Transport Category	Transport Category No data available.		No data available.		
ADR Multiplier	No data available.	No data available.	No data available.		
IMDG Segregation Code	No data available.	No data available.	No data available.		

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 11: Health Effects - Skin information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 27-4388-8
 Version number:
 16.01

 Revision date:
 07/07/2021
 Supersedes date:
 18/06/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Perfect-It 50383, 51302, 51308 Ultrafine Polish

Product Identification Numbers

UU-0016-6332-5 UU-0016-6334-1 UU-0108-8136-3

7100062883 7100057579 7100224683

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Notes on labelling

Nota L applied to CAS# 64741-88-4.

2.3. Other hazards

Contains a substance that meets the criteria for PBT according to Regulation (EC) No 1907/2006, Annex XIII Contains a substance that meets the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
Non-Hazardous Ingredients	Trade Secret	40 - 70	Substance not classified as hazardous			
Dodecamethylcyclohexasiloxane	(CAS-No.) 540-97-6 (EC-No.) 208-762-8	10 - 30	Substance not classified as hazardous			
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01- 2119456620-43	14 - 16	Asp. Tox. 1, H304 EUH066			
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	3 - 7	Substance with a national occupational exposure limit			
Distillates (petroleum), solvent-refined heavy paraffinic	(CAS-No.) 64741-88-4 (EC-No.) 265-090-8	1 - 5	Nota L Asp. Tox. 1, H304 EUH066			
Glycerol	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	<= 1	Substance with a national occupational exposure limit			
Decamethylcyclopentasiloxane	(CAS-No.) 541-02-6 (EC-No.) 208-764-9	0.1 - 1	Aquatic Chronic 4, H413			
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.1	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400,M=10			

3M Perfect-It 50383, 51302, 51308 Ultrafine Polish

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
` /	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.05%) Skin Sens. 1, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

No need for first aid is anticipated.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring combustion.Carbon dioxide.During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments
Aluminium oxide 1344-28-1 UK HSC TWA(as respirable dust):4
mg/m3;TWA(as inhalable
dust):10 mg/m3
Glycerol 56-81-5 UK HSC TWA(as mist):10 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK

HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.

Specific Physical Form:Thixotropic liquid.ColourLight Blue

Odor Solvent
Odour threshold No data available.

Melting point/freezing pointNot applicable.Boiling point/boiling rangeNo data available.Flammability (solid, gas)Not applicable.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.

Flash point >= 110 °C [Test Method:Closed Cup]

Autoignition temperature Not applicable.

3M Perfect-It 50383, 51302, 51308 Ultrafine Polish

Decomposition temperature

Kinematic Viscosity Water solubility

Solubility- non-water

Partition coefficient: n-octanol/water Vapour pressure

Density

Relative density

Relative Vapor Density

No data available.

7.5 - 8.5 Units not available or not applicable.

12,623.4906695939 mm²/sec

Appreciable

No data available. No data available. No data available.

0.9 - 1 kg/l

0.911 - 1.007 [*Ref Std:*WATER=1]

No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rate

Percent volatile

No data available. No data available.

15.9 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

High shear and high temperature conditions

Sparks and/or flames.

Temperatures above the boiling point.

10.5 Incompatible materials

Alkali and alkaline earth metals.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	Rat	LD50 > 5,000
Glycerol	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerol	Ingestion	Rat	LD50 > 5,000 mg/kg
Decamethylcyclopentasiloxane	Dermal	Rabbit	LD50 > 15,000 mg/kg
Decamethylcyclopentasiloxane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 8.7 mg/l
Decamethylcyclopentasiloxane	Ingestion	Rat	LD50 > 24,134 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 454 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value		
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation		

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		Minimal irritation
Aluminium oxide	Rabbit	No significant irritation
Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Minimal irritation
Glycerol	Rabbit	No significant irritation
Decamethylcyclopentasiloxane	Rabbit	No significant irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Mild irritant
Glycerol	Rabbit	No significant irritation
Decamethylcyclopentasiloxane	Rabbit	No significant irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea	Not classified
	pig	
Distillates (petroleum), solvent-refined heavy paraffinic	Guinea	Not classified
	pig	
Glycerol	Guinea	Not classified
	pig	
Decamethylcyclopentasiloxane	Mouse	Not classified
1,2-benzisothiazol-3(2H)-one	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic		
Aluminium oxide	In Vitro	Not mutagenic		
Distillates (petroleum), solvent-refined heavy paraffinic	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Decamethylcyclopentasiloxane	In Vitro	Not mutagenic		
Decamethylcyclopentasiloxane	In vivo	Not mutagenic		
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic		
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%		Not	Not carcinogenic
aromatics	specified.	available	
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Glycerol	Ingestion	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Decamethylcyclopentasiloxane	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
Glycerol	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not classified for development	Rat	NOAEL 2.43 mg/l	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), solvent-refined heavy paraffinic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
1,2-benzisothiazol-3(2H)- one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasil oxane	Ingestion	endocrine system liver respiratory system nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for	Human	NOAEL Not available	occupational exposure

			classification			
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Distillates (petroleum), solvent-refined heavy paraffinic	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.21 mg/l	28 days
Glycerol	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerol	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Decamethylcyclopentasilo xane	Dermal	hematopoietic system eyes	Not classified	Rat	NOAEL 1,600 mg/kg/day	28 days
Decamethylcyclopentasilo xane	Inhalation	hematopoietic system respiratory system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 2.42 mg/l	2 years
Decamethylcyclopentasilo xane	Ingestion	liver immune system respiratory system heart hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
Distillates (petroleum), solvent-refined heavy paraffinic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

3.5 4 1 1	C A C II		TT.	-		TD / 1/
Material	(CAS#	(Organism	Tvpe	Exposure	Lest endnoint	Test result
1,144,61141	0110 "	015	1 * J P C	Liposuic	1 cst chapoint	I est I estile

Dodecamethylcyclohex asiloxane	540-97-6	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Dodecamethylcyclohex asiloxane	540-97-6	Green algae	Experimental	72 hours	EC50	>100 mg/l
Dodecamethylcyclohex asiloxane	540-97-6	Fathead minnow	Experimental	49 days	NOEC	100 mg/l
Dodecamethylcyclohex asiloxane	540-97-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Dodecamethylcyclohex asiloxane	540-97-6	Water flea	Experimental	21 days	NOEC	100 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Fathead minnow	Estimated	96 hours	LL50	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Water flea	Estimated	48 hours	EC50	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Green algae	Experimental	96 hours	EL50	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Green algae	Experimental	96 hours	NOEL	100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Water flea	Experimental	21 days	NOEL	100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Activated sludge	Experimental	3 hours	EC50	>2,000 mg/l
Decamethylcyclopentas iloxane	541-02-6	Green Algae	Experimental	96 hours	EC50	>100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Water flea	Experimental	48 hours	EC50	>100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Green Algae	Experimental	96 hours	NOEC	100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Rainbow trout	Experimental	90 days	NOEC	100 mg/l
Decamethylcyclopentas iloxane	541-02-6	Water flea	Experimental	21 days	NOEC	100 mg/l
Glycerol	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Glycerol	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l

Dagg. 11 of 1

Glycerol	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	EC50	0.11 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Pacific oyster	Experimental	48 hours	EC50	0.062 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Dodecamethylcyclohexasilo xane	540-97-6	Experimental Biodegradation	28 days	CO2 evolution	4.47 % weight	OECD 310 CO2 Headspace
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Aluminium oxide	1344-28-1	Data not availbl- insufficient			N/A	
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Experimental Biodegradation	28 days	CO2 evolution	22 % weight	OECD 301B - Modified sturm or CO2
Decamethylcyclopentasilox ane	541-02-6	Experimental Photolysis		Photolytic half-life (in air)	20.4 days (t 1/2)	Non-standard method
Decamethylcyclopentasilox ane	541-02-6	Experimental Hydrolysis		Hydrolytic half-life	66 days (t 1/2)	Non-standard method
Decamethylcyclopentasilox ane	541-02-6	Experimental Biodegradation	28 days	CO2 evolution	0.14 % weight	OECD 310 CO2 Headspace
Glycerol	56-81-5	Experimental Biodegradation	14 days	BOD	63 % BOD/ThBOD	OECD 301C - MITI test (I)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Dodecamethylcyclohexasil oxane	540-97-6	Experimental BCF - Fathead Minnow	49 days	Bioaccumulation factor	1160	OECD 305E - Bioaccumulation flow- through fish test
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Estimated Bioconcentration		Bioaccumulation factor	7.5	Estimated: Bioconcentration factor
Decamethylcyclopentasilox ane	541-02-6	Experimental BCF - Fathead Minnow	35 days	Bioaccumulation factor	7060	OECD 305E - Bioaccumulation flow- through fish test
Glycerol	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Non-standard method
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental BCF - Bluegill	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Glycerol	56-81-5	Estimated	Koc	<1 l/kg	Episuite TM
		Mobility in Soil			
1,2-benzisothiazol-3(2H)-	2634-33-5	Experimental	Koc	ERROR: Length	OECD 121 Estim. of Koc by
one		Mobility in Soil		cannot be greater	HPLC
				than the length of	
				the string.	

12.5. Results of the PBT and vPvB assessment

Ingredient	CAS Nbr	PBT/vPvB status
Decamethylcyclopentasiloxane	541-02-6	Meets REACH PBT criteria
Decamethylcyclopentasiloxane	541-02-6	Meets REACH PBT criteria
Decamethylcyclopentasiloxane	541-02-6	Meets REACH PBT criteria
Decamethylcyclopentasiloxane	541-02-6	Meets REACH PBT criteria
Dodecamethylcyclohexasiloxane	540-97-6	Meets REACH PBT criteria
Dodecamethylcyclohexasiloxane	540-97-6	Meets REACH PBT criteria
Dodecamethylcyclohexasiloxane	540-97-6	Meets REACH PBT criteria
Dodecamethylcyclohexasiloxane	540-97-6	Meets REACH PBT criteria

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)

14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Tunnel Code	No data available.	Not applicable.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
ADR Transport Category	No data available.	No data available.	No data available.
ADR Multiplier	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users

of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient CAS Nbr Decamethylcyclopentasiloxane 541-02-6

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Authorization status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

Ingredient CAS Nbr Decamethylcyclopentasiloxane 541-02-6 Dodecamethylcyclohexasiloxane 540-97-6

Authorization status: listed in the Candidate List of Substances of Very High Concern for Authorization

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H400	Very toxic to aquatic life.	
H413	May cause long lasting harmful effects to aquatic life.	

Revision information:

Section 9: Property description for optional properties information was modified.

Annex

EUH066

1. Title		
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6;	
Exposure Scenario Name	Professional Use of Coatings	
Lifecycle Stage	Widespread use by professional workers	
Contributing activities	PROC 10 -Roller application or brushing	
	ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or	
	onto article, indoor)	

measures apply: General risk management measures: Human health: None needed;		ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or	
2. Operating Conditions Physical state:Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; When the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;		, , , , , , , , , , , , , , , , , , ,	
Operating Conditions Physical state:Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;	Processes, tasks and activities covered	Application of product.	
General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;			
Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;	Operating Conditions	Physical state:Liquid.	
Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;			
Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;		Duration of exposure per day at workplace [for one worker]: 8 hours/day;	
Indoor use; Outdoor use; Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;			
Outdoor use; What is a management measures apply: General risk management measures: Human health: None needed;		Frequency of exposure at workplace [for one worker]: Daily;	
Risk management measures Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed;		Indoor use;	
measures apply: General risk management measures: Human health: None needed;		Outdoor use;	
measures apply: General risk management measures: Human health: None needed;			
General risk management measures: Human health: None needed;	Risk management measures	Under the operational conditions described above the following risk management	
Human health: None needed;			
None needed;			
· · · · · · · · · · · · · · · · · · ·		11411411	
Environmental			
		Environmental:	
None needed;		None needed;	
Weste management measures Avoid release to the environment. Defer to special instructions / sefety data sheet	Wasta managamant massures	Avoid release to the environment Defer to special instructions / sefety data sheet:	
Waste management measures Avoid release to the environment. Refer to special instructions / safety data sheet	waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;	
3. Prediction of exposure	3. Prediction of exposure		
Prediction of exposure Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted	Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.	

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 19-1306-0
 Version number:
 15.00

 Revision date:
 09/09/2021
 Supersedes date:
 09/04/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Polish Rosa

Product Identification Numbers

GC-8009-8956-5

7000083980

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Car polish

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 E Mail: tox.uk@mmm.com Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms





Ingredients:

Ingredient CAS Nbr EC No. % by Wt Naphtha (petroleum), hydrotreated heavy 64742-48-9 265-150-3 25 - 50

HAZARD STATEMENTS:

Causes skin irritation. H315

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Notes on labelling

Nota P applied to CAS# 64742-48-9

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)		Classification according to Regulation (EC) No. 1272/2008 [CLP]
	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	30 - 80	Substance not classified as hazardous
Naphtha (petroleum), hydrotreated heavy	(CAS-No.) 64742-48-9	25 - 50	Asp. Tox. 1, H304

	(EC-No.) 265-150-3		Nota P Aquatic Chronic 2, H411 Skin Irrit. 2, H315 STOT SE 3, H336
Wax (mixture)	Trade Secret	1 - 10	Substance not classified as hazardous
Siloxanes and silicones, di-Me	(CAS-No.) 63148-62-9	1 - 10	Substance not classified as hazardous
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	1 - 10	Substance with a national occupational exposure limit
Emulsifier	Trade Secret	< 2	Substance not classified as hazardous
Oleic Acid	(CAS-No.) 112-80-1 (EC-No.) 204-007-1	< 2	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure

demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Kaolin 1332-58-7 UK HSC TWA (as respirable dust): 2

UK HSC : UK Health and Safety Commission

 mg/m^3

3M Polish Rosa

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.ColourRed

Odor Characteristic Odour Odour threshold No data available.

3M Polish Rosa

Melting point/freezing pointNot applicable.Boiling point/boiling rangeNot applicable.Flammability (solid, gas)Not applicable.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.Flash point>=62 °C

Flash point >=62 °C
Autoignition temperature 240 °C

Decomposition temperaturepH

No data available.

Kinematic Viscosity 2,473.68421052632 mm²/sec **Water solubility** *No data available.*

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNo data available.

Density 0.95 kg/l

Relative density0.95 [Ref Std: WATER=1] **Relative Vapor Density**>=1 [Ref Std: AIR=1]

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

Evaporation rate

No data available.

Percent volatile

No data available.

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Strong acids.

10.6 Hazardous decomposition products

SubstanceConditionformaldehydeNot specified.Carbon monoxideNot specified.Carbon dioxide.Not specified.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition,

statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Oleic Acid	Dermal	Guinea	LD50 > 3,000 mg/kg
		pig	
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Kaolin	Professio	No significant irritation
	nal	
	judgemen	

	t	
Oleic Acid	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Kaolin	Professio	No significant irritation
	nal	
	judgemen	
	t	
Oleic Acid	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Guinea	Not classified
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route Value			
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic		
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Oleic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not specified.	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

teproductive and/or Developmental Effects							
Name	Route	Value	Species	Test result	Exposure Duration		
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis		

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration

Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphtha (petroleum), hydrotreated heavy	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Oleic Acid	Ingestion	liver immune system	Not classified	Rat	NOAEL 2,250 mg/kg/day	108 weeks
Oleic Acid	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,550 mg/kg/day	108 weeks

Aspiration Hazard

 115 MI WINI I III W				
Name	Value			
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard			

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Green Algae	Estimated	72 hours	EL50	3.1 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Green Algae	Estimated	72 hours	NOEL	0.5 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			N/A
Oleic Acid	112-80-1		Data not available or insufficient for classification			N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Estimated Biodegradation	28 days	BOD	10 % BOD/ThBOD	OECD 301D - Closed bottle test
Kaolin	1332-58-7	Data not availbl- insufficient			N/A	
Siloxanes and silicones, di- Me	63148-62-9	Data not availbl- insufficient			N/A	
Oleic Acid	112-80-1	Experimental Biodegradation	28 days	BOD	78 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oleic Acid	112-80-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Estimated Mobility in Soil	Koc	800 l/kg	Episuite TM
Oleic Acid	112-80-1	Estimated Mobility in Soil	Koc	1,600 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 15*

Aqueous liquid waste containing adhesives or sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S.(HYDROTREATED HEAVY NAPHTHA (PETROLEUM))	LIQUID, N.O.S.(HYDROTREATED HEAVY NAPHTHA (PETROLEUM))	SUBSTANCE, LIQUID, N.O.S.(HYDROTREATED HEAVY NAPHTHA (PETROLEUM))
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.

14.7 Transport in bulk	No data available.	No data available.	No data available.
according to Annex II of Marpol 73/78 and IBC Code			
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Tunnel Code	(-)	Not applicable.	Not applicable.
ADR Classification Code	M6	Not applicable.	Not applicable.
ADR Transport Category	4	Not applicable.	Not applicable.
ADR Multiplier	0	0	0
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information:

Label: CLP Precautionary - Disposal information was deleted. Label: CLP Precautionary - General information was deleted.

3M Polish Rosa

- Section 14 Classification Code Regulation Data information was modified.
- Section 14 Control Temperature Regulation Data information was modified.
- Section 14 Emergency Temperature Regulation Data information was modified.
- Section 14 Other Dangerous Goods Regulation Data information was modified.
- Section 14 Segregation Regulation Data information was modified.
- Section 14 Transport Category Regulation Data information was modified.
- Section 14 Transport in bulk Regulation Data information was modified.
- Section 14 Transport Not Permitted Main Heading information was deleted.
- Section 14 Transport Not Permitted Regulation Data information was deleted.
- Section 14 Tunnel Code Regulation Data information was modified.
- Section 15: Regulations Inventories information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 27-8119-3
 Version number:
 15.03

 Revision date:
 07/07/2021
 Supersedes date:
 18/06/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 80349, 51301, 51306 Perfect-It Extra Fine Plus

Product Identification Numbers

GC-8010-4166-3 GC-8010-4167-1 UU-0016-6331-7 UU-0016-6335-8 UU-0108-7968-0

7000084862 7000034473 7100057580 7100064019 7100224682

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Non-Hazardous Ingredients	Mixture	50 - 70	Substance not classified as hazardous
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01- 2119456620-43	15 - 40	Asp. Tox. 1, H304 EUH066
Aluminium Oxide (non-fibrous)	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	5 - 10	Substance with a national occupational exposure limit
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8 (REACH-No.) 01- 2119487078-27	1 - 5	Asp. Tox. 1, H304
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 920-107-4	1 - 5	Asp. Tox. 1, H304 EUH066
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400,M=10

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
` /	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.05%) Skin Sens. 1, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or

bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Aluminium Oxide (non-fibrous) 1344-28-1 UK HSC TWA(as respirable dust):4 mg/m3;TWA(as inhalable

dust):10 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeNitrile rubber.No data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:SlurryColourWhiteOdorSolvent

Odour thresholdNo data available.Melting point/freezing pointNot applicable.Boiling point/boiling rangeNo data available.Flammability (solid, gas)Not applicable.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.

Flash point > 125 °C [Test Method: Setaflash]

3M 80349, 51301, 51306 Perfect-It Extra Fine Plus

Autoignition temperature Decomposition temperature

pН

Kinematic Viscosity Water solubility Solubility- non-water

Partition coefficient: n-octanol/water

Vapour pressure

Density

Relative density

Relative Vapor Density

No data available. No data available.

8 - 8.5 Units not available or not applicable.

20,942.4083769634 mm²/sec

No data available. No data available. No data available. No data available.

0.917 g/cm3 - 0.993 g/cm3

0.917 - 0.993 [*Ref Std*:WATER=1]

No data available.

296.9 g/l

No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

Evaporation rate

Percent volatile 15.2 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

High shear and high temperature conditions

10.5 Incompatible materials

Alkali and alkaline earth metals.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance **Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2%	Inhalation-	Professio	LC50 estimated to be 20 - 50 mg/l
aromatics	Vapour	nal judgeme nt	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 454 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

5111 C 011 0 0 1 0 1 1 1 1 1 1 1 1 1 1 1					
Name	Species	Value			
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation			

3M 80349, 51301, 51306 Perfect-It Extra Fine Plus

Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Minimal irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Mild irritant
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea	Not classified
	pig	
White mineral oil (petroleum)	Guinea	Not classified
	pig	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Guinea	Not classified
	pig	
1,2-benzisothiazol-3(2H)-one	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%	Not	Not	Not carcinogenic
aromatics	specified.	available	
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2%	Not	Not	Not carcinogenic
aromatics	specified.	available	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation

Dagg. 0 of 16

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	premating & during gestation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

\sim	pecific furget organ roadery single exposure							
	Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	
H	1.2-benzisothiazol-3(2H)-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	Duration	
	one	Illiaiation	respiratory irritation	data are not sufficient for	health	available		
				classification	hazards			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non- fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Estimated	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <	920-107-4	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l

2% aromatics						
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Estimated	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	NOEL	>100 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	EC50	0.11 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Pacific oyster	Experimental	48 hours	EC50	0.062 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Aluminium Oxide (non- fibrous)	1344-28-1	Data not availbl- insufficient			N/A	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Estimated Biodegradation	28 days	BOD	67.6 % BOD/ThBOD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-	926-141-6	Data not available	N/A	N/A	N/A	N/A
alkanes, isoalkanes,		or insufficient for				
cyclics, <2% aromatics		classification				
Aluminium Oxide (non-	1344-28-1	Data not available	N/A	N/A	N/A	N/A

fibrous)		or insufficient for classification				
Hydrocarbons, C12-C15, n- alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n- alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental BCF - Bluegill	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material (Cas No.	Test type	Study Type	Test result	Protocol
1,2-benzisothiazol-3(2H)- one		Experimental Mobility in Soil		ERROR: Length cannot be greater than the length of the string.	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Tunnel Code	No data available.	Not applicable.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
ADR Transport Category	No data available.	No data available.	No data available.
ADR Multiplier	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.

Revision information:

Section 9: Property description for optional properties information was modified.

Annex

DITTOCC

1. Title	
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6; Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 920-107-4;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Processes, tasks and activities covered	Application of product with microfiber towel, cloth, or brush
2. Operational conditions and risk mana	gement measures
Operating Conditions	Physical state:Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: Daily; Emission days per year: 300 days/year;
	Frequency of exposure at workplace [for one worker]: 8 hours/day;

	Indoor use; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;
3. Prediction of exposure	·
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Processes, tasks and activities covered	Application of product.
2. Operational conditions and risk mana	
Operating Conditions	Physical state:Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 300 days per year; Frequency of exposure at workplace [for one worker]: Daily; Indoor use; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;
3. Prediction of exposure	•
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance

3M 80349, 51301, 51306 Perfect-It Extra Fine Plus
volume tracking, and potential substance registration.
volume tracking, and potential substance registration.
3M United Kingdom MSDSs are available at www.3M.com/uk

Page: 16 of 16