

# QUARTZ

46120

## Putty Light

TDS No.: 4403 EN // TDS Date: V1-17.1.2010

<b>Product</b>	Putty Light incl. hardener
<b>Colour</b>	Beige
<b>Product description</b>	Up to 40 % higher sanding efficiency compared to universal putty. For filling deep holes and uneven surfaces. Very fast and easy sanding. Can be sprayed over with all standard paint systems after sanding.
<b>Use for</b>	Passenger cars, trucks, railway carriages and other applications.
<b>Substrate</b>	Steel, aluminum, sanded OEM paint, wood, polyester laminates.
<b>Mixing ratio</b>	2-3 % (by weight) of hardener paste
<b>Hardener</b>	Hardener paste red, storage 20 months, incl. in packing.
<b>Pot life</b>	3-4 minutes
<b>Drying time</b>	Ready to sand after 15-20 min at 20 °C The drying time depends on ambient temperature, air humidity and the applied layer thickness.
<b>Sanding</b>	Dry sanding with P80-P280
<b>Specific weight</b>	1,3 kg packing, 1,3 g/ccm
<b>Classification</b>	UN3269, ADR 3/III LQ, 2004/42/II(b)(250)< 250
<b>Shelf life</b>	8-12 months at 18-20 °C in closed can Store in a dry place and away from sunlight. Maximum air humidity 60 %.
<b>Special instructions</b>	Polyester putties are sensitive to humidity and should only be dry sanded. Adding too much hardener to the putty can effect the colour stability of the topcoat. Application temperature 5 °C minimum.

Information given in this sheet represent the best of our knowledge. Please verify before use if this product is suitable for your application.