

Safety data sheet
according to 1907/2006/EC, Article 31
Version number 1

MSDS6401
Revision: 26.06.2014

*

1 Identification of the substance/mixture and of the company/undertaking**· 1.1 Product identifier**

· Trade name: **1K Black Mat**

· Article number: 15050

· 1.2 Relevant identified uses of the substance or mixture and uses advised against --

· Application of the substance / the mixture Lacquer

· 1.3 Details of the supplier of the safety data sheet**· Manufacturer/Supplier:**

Quartz Refinish Limited, Morleys Group
250 Osmaston Road, Derby
DE23 8LB, England

Phone: +44 1332 611893

Fax: +44 1332 331611

· E-mail address of the competent person responsible for the Safety Data Sheet: info@spraygunsdirect.co.uk

· Further information obtainable from: Sprayguns Direct Limited, Morleys Group

· 1.4 Emergency telephone number: +44 1332 611893

*

2 Hazards identification**· 2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

GB

Trade name: 1K Black Mat

(Contd. of page 1)

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

acetone

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.











*

3 Composition/information on ingredients

· **3.2 Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**


















CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone  Xi R36;  F R11 R66-67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67  Flam. Liq. 3, H226;  STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	10-<12.5%

(Contd. on page 3)

GB

Trade name: 1K Black Mat

(Contd. of page 2)

CAS: 9004-70-0	cellulose nitrate  F R11  Flam. Sol. 1, H228	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	2.5-<5.0%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol  Xi R36;  F R11 R67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%
CAS: 64742-94-5 EINECS: 265-198-5 Reg.nr.: 01-2119510128-50	Solvent naphtha (petroleum), heavy arom.  Xn R65  Asp. Tox. 1, H304	<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Kohlenwasserstoffe, C9, Aromate  Xn R65;  Xi R37;  N R51/53 R10-66-67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H335-H336	≤0.5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.
For the wording of the listed risk phrases refer to section 16.

*

4 First aid measures

4.1 Description of first aid measures

- After inhalation:** Supply fresh air; consult doctor in case of complaints.
- After skin contact:** Generally the product does not irritate the skin.
- After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim.
Vaten met water afkoelen.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters -

Protective equipment: No special measures required.

*

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

GB

Trade name: 1K Black Mat

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:**
Do not flush with water or aqueous cleansing agents
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

7 Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2B
- **7.3 Specific end use(s)** No further relevant information available.

*

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:	
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
106-97-8 butane	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
67-63-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

GB

Trade name: 1K Black Mat

(Contd. of page 4)

Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.
Otherwise, filter class A / P2 or self contained.

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

· **Eye protection:** Safety glasses

*

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Black

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 180 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 13.0 Vol %

· **Vapour pressure at 20 °C:** 8300 hPa

· **Density at 20 °C:** 0.78 g/cm³

· **Relative density** Not determined.

(Contd. on page 6)

GB

Trade name: 1K Black Mat

(Contd. of page 5)

· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC-(EU)	---
	645.2 g/l
· VOC-EU%	82.46 %
· 9.2 Other information	No further relevant information available.

* 10 Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

* 11 Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification:		
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

* 12 Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

GB

Trade name: 1K Black Mat

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

*

13 Disposal considerations



- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

*

14 Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	UN1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No

(Contd. on page 8)

GB

Trade name: 1K Black Mat

(Contd. of page 7)

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: 	<p>Warning: Gases.</p> <p>-</p> <p>F-D,S-U</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN1950, AEROSOLS, 2.1</p>

* **15 Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H220 Extremely flammable gas.
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H228 Flammable solid.
 - H280 Contains gas under pressure; may explode if heated.
 - H304 May be fatal if swallowed and enters airways.
 - H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H411 Toxic to aquatic life with long lasting effects.
 - R10 Flammable.
 - R11 Highly flammable.
 - R12 Extremely flammable.
 - R36 Irritating to eyes.
 - R37 Irritating to respiratory system.
 - R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - R65 Harmfull: may cause lung damage if swallowed
 - R66 Repeated exposure may cause skin dryness or cracking.
 - R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:**

Sprayguns Direct Limited, Morleys Group
250 Osmaston Road, Derby
DE23 8LB, England

Phone: +44 1332 611893
Fax: +44 1332 331611

(Contd. on page 9)

GB



Trade name: **1K Black Mat**

(Contd. of page 8)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Flam. Sol. 1: Flammable solids, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

GB