

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

MSDS6402 Revision: 26.06.2014

*

1 Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

[•] Trade name: 1K Spray Blender

• Article number: 15030

- \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Lacquer
- \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Quartz Refinish Limited, Morleys Group 250 Osmaston Road, Derby DE23 8LB, England

Phone: +44 1332 611893 Fax: +44 1332 331611

E-mail address of the competent person responsible for the Safety Data Sheet: info@spraygunsdirect.co.uk Further information obtainable from: Sprayguns Direct Limited Morleys Group

• 1.4 Emergency telephone number: +44 1332 611893

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

- R12: Extremely flammable.
- · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- Warning! Pressurized container.
- Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Danger
- Hazard statements
- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- · Precautionary statements
- *P101 If medical advice is needed, have product container or label at hand.*

(Contd. on page 2) GB



Version number 2

Revision: 26.06.2014

(Contd. of page 1)

Trade name: 1K Spray Blender

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211Do not spray on an open flame or other ignition source.
- P251Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

• Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether F + R12 Flam. Gas 1, H220; Press. Gas, H280	50-<75%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 Flam. Liq. 3, H226; (1) STOT SE 3, H336	12.5-<20%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 Image: R10	12.5-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32		5-<10%
	Flam. Liq. 3, H226; (1) Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene Xn R20; 6 F R11 Flam. Liq. 2, H225; 1 Acute Tox. 4, H332	2.5-<5.0%
CAS: 70657-70-4 EINECS: 274-724-2 Reg.nr.: 02-2119857599-15	2-methoxypropyl acetate Z T Repr. Cat. 2 R61; X IR37 R10	≤0.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

*

4 First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Version number 2

Revision: 26.06.2014

Trade name: 1K Spray Blender

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim. Vaten met water afkoelen.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Store in a cool location.
- Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingr	edients with limit values that require monitoring at the workplace:
115-	10-6 dimethyl ether
WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm



Version number 2

Revision: 26.06.2014

Trade name: 1K Spray Blender

100		(Contd. of page
	86-4 n-butyl acetate	
WEL	L Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m ³ , 150 ppm	
108-0	65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm	
	Long-term value: 274 mg/m ³ , 50 ppm	
	Sk	
1330	-20-7 xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m ³ , 100 ppm	
	Long-term value: 220 mg/m ³ , 50 ppm	
	Sk; BMGV	
100-4	41-4 ethylbenzene	
WEL	Short-term value: 552 mg/m ³ , 125 ppm	
	Long-term value: 441 mg/m ³ , 100 ppm	
	Sk	
· Ingre	edients with biological limit values:	
1330	0-20-7 xylene, mixture of isomers	
BMG	GV 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min • Eye protection: Safety glasses

> GB (Contd. on page 5)



*

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.06.2014

Trade name: 1K Spray Blender

(Contd. of page 4)

9 Physical and chemical proper	rties
• 9.1 Information on basic physical a	and chemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	Transparent
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	235 °C
• Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	5200 hPa
· Density at 20 °C:	0.76 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
<i>VOC-(EU)</i>	
	753.1 g/l
· VOC-EU%	98.87 %
• 9.2 Other information	No further relevant information available.

* 10 Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6) _{GB}



Version number 2

Revision: 26.06.2014

Trade name: 1K Spray Blender

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:		
1330-20-7	1330-20-7 xylene, mixture of isomers	
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information: Vapours have narcotic effect.

* 12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1330-20-7 xylene, mixture of isomers

EC50 (24h) >175 mg/l (bacteria)

EC50 / 48h 3.82 mg/l (daphnia magna / Wasserfloh)

EC50/72h 4.7 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

* 13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

(Contd. on page 7) GB



*

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.06.2014

(Contd. of page 6)

Trade name: 1K Spray Blender

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	UN1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
14.7 Transport in bulk according to Annex MARPOL73/78 and the IBC Code	: II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
	Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity

GB (Contd. on page 8)





Version number 2

Revision: 26.06.2014

Phone: +44 1332 611893

Fax: +44 1332 331611

Trade name: 1K Spray Blender

(Contd. of page 7)

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360D May damage the unborn child.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- *R61 May cause harm to the unborn child.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67* Vapours may cause drowsiness and dizziness.

· Department issuing MSDS:

Sprayguns Direct Limited Morleys Group 250 Osmaston Road, Derby DE23 8LB, England

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3