



UNIVERSAL PUTTY

Product code 46100
TDS code TDS401-EN
TDS date V1 - 24.1.2010

Product	⇒ Universal Putty beige incl. hardener
Product description	⇒ universal polyester-putty ⇒ for use on galvanized, aluminium and bare metal surfaces ⇒ for passenger cars, trucks, railway carriages and other vehicles ⇒ multi-purpose putty due to creamy consistency which allows fine, smooth, pinhole-free application combined with high filling capacity ⇒ fast drying and easy and quick sanding ⇒ can be sprayed over with all standard paint systems after sanding
Use for	⇒ car and truck repair jobs, coarse as well as fine filling
Substrate	⇒ galvanized or bare steel, aluminium, sanded OEM paint ⇒ surface must be clean, dry and free of grease
Mixing ratio	⇒ 2-3% (by weight) of hardener paste
Hardener	⇒ hardener paste red, storage 20 months, incl. in packing
Pot life	⇒ 3-4 minutes
Drying time	⇒ ready to sand after 15-20 min. at 20°C
Sanding	⇒ dry sanding with P80-P280
Special instructions	⇒ polyester putties are sensitive to humidity and should only be dry sanded. Adding too much hardener to the putty can effect the colour stability of the topcoat ⇒ application temperature 5° C minimum
Shelf life	⇒ 8-12 months at 18-20 °C in closed can
Weight	⇒ 2,0 kg packing, 1,8 g / ccm
Classification	⇒ UN3269, ADR 3/III LQ, 2004/42/IIIB(b)(250)< 250