

Œ

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Colad Easy2Check

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Underfloor protection

#### **Uses advised against:**

No information available at present.

### 1.3 Details of the supplier of the safety data sheet

EMM International BV Marsweg 59, NL-8013 PE Zwolle Telephone: +31-38-4676600, Fax: +31-38-4676699

info@emm.com www.emm.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone

#### **Emergency information services / official advisory body:**

---

## Telephone number of the company in case of emergencies:

Tel.: +31-38-4676600 (Week days available between 08:00 & 17:00)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

F+,Extremely flammable

Xi, Irritant, R38

N, Dangerous for the environment, R51-53

R67

#### 2.2 Label elements

## 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check



#### **Hazard statement**

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

#### Prevention

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

#### Response

P312-Call a POISON CENTER/doctor if you feel unwell.

#### Storage

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible. Naphtha (petroleum), heavy alkylate

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## **SECTION 3: Composition/information on ingredients**

Aerosol

## 3.1 Substance

## n.a. 3.2 Mixture

Naphtha (petroleum), heavy alkylate	
Registration number (REACH)	
Index	649-275-00-4
EINECS, ELINCS, NLP	265-067-2
CAS	CAS 64741-65-7
content %	70-80
Classification according to Directive 67/548/EEC	Flammable, R10
	Irritant, Xi, R38
	Dangerous for the environment, N, R51
	Dangerous for the environment, R53
	Harmful, Xn, R65
	R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Aquatic Chronic 2, H411

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.



GB)

Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named

here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the eyes

Drying of the skin.

Dermatitis (skin inflammation)

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Mental confusion

Unconsciousness

Ingestion:

Nausea

Vomiting

Danger of aspiration

oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

## 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media

CO<sub>2</sub>

Dry extinguisher

Water jet spray

Alcohol resistant foam



Œ

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

#### Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

#### 6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities



. (B)

Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

## 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Naphtha (petrole	Naphtha (petroleum), heavy alkylate						
WEL-TWA: 1200 mg/m3 (>= C	7 normal and	WEL-STEL:						
branched chain alkanes)								
BMGV:				Other information:				
Chemical Name	Petroleum gases,	liquified, sweet	ened			Content %:		
WEL-TWA: 1000 ppm (1750 mg	g/m3) (Liquefied	WEL-STEL:	1250 ppm (2180	0 mg/m3) (Liquefied				
petroleum gas (LPG))		petroleum gas	s (LPG))					
BMGV:				Other information:				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

## 8.2 Exposure controls

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

> 0,5

Permeation time (penetration time) in minutes:

> 240

<sup>\*\* =</sup> The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

The breakthrough times determined in accordance with EN 374 Part III were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection: Normally not necessary. If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Colour: Yellow, Brown Odour. Characteristic Odour threshold: Not determined pH-value: Not determined

Melting point/freezing point: ~-60--50 °C (Active substance)

Initial boiling point and boiling range: >150<250 °C (EN ISO 3405, Active substance )

Flash point: -92,37 °C Not determined Evaporation rate: Flammability (solid, gas): Not determined Lower explosive limit: 0,8 Vol-% Upper explosive limit: 6 Vol-%

Vapour pressure: >7<9 hPa (38°C, EN 13016, Active substance)

Vapour density (air = 1): Not determined

>750<770 kg/m3 (15°C, ISO 12185, Active substance ) Density:

Bulk density: Not determined Solubility(ies):

Water solubility:

Insoluble, Active substance

Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined

>1,4<1,5 mm2/s (Active substance) Viscosity:

Explosive properties: Possible build up of explosive/highly flammable vapour/air

> mixture. Nο

Oxidising properties: 9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined



Œ

Page 7 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

## 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

## 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

Possibly more information on health effects, see Section 2.1 (classification).

Colad Easy2Check Toxicity/effect	Endpoi	Value	Unit	Organism	Test method	Notes
•	nt .					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according
						to calculation
		1				procedure.

	Petroleum gases, liquified, sweetened							
	Toxicity/effect	Endpoi	Value	Unit	Organism	Test method	Notes	
		nt						
1		•	•	•		•	•	



(B)

Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat	Vapours

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Colad Easy2Check							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							n.d.a.
degradability:							
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT and							n.d.a.
vPvB assessment							
Other adverse effects:							n.d.a.

Petroleum gases, liquified, sweetened								
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Toxicity to fish:	LC50	96h	11,07	mg/l				
Toxicity to daphnia:	LC50	48h	14,22	mg/l				
Toxicity to algae:	EC50	96h	4,71	mg/l				
Results of PBT and							No PBT substance, No	
vPvB assessment							vPvB substance	

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by dangerous substances

Do not perforate, cut up or weld uncleaned container.

## **SECTION 14: Transport information**

**General statements** 

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name: UN 1950 AEROSOLS

Transport hazard class(es):

Packing group:

Classification code:

5F







(B)

Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014

Colad Easy2Check

LQ (ADR 2013): 1 L LQ (ADR 2009): 2

Environmental hazards: environmentally hazardous

Tunnel restriction code: D

Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS (NAPHTHA (PETROLEUM))

Transport hazard class(es):

2.1
Packing group:

EmS: F-D, S-U

Marine Pollutant: Yes

Environmental hazards: environmentally hazardous

Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es): 2.1

Packing group: -

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Yes

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

VOC (1999/13/EC): 720 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

These details refer to the product as it is delivered.

Revised sections: n.a.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Evaluation method used
Classification according to calculation procedure.
Classification according to calculation procedure.
Classification according to calculation procedure.
Classification based on test data.
Classification according to calculation procedure.
Classification based on test data.









Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

10 Flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Asp. Tox. — Aspiration hazard

Flam. Liq. — Flammable liquid

## Any abbreviations and acronyms used in this document:

AC **Article Categories** 

acc., acc. to according, according to

ACGIHAmerican Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approximately approx. Article number Art., Art. no.

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

Bioconcentration factor BCF

BGV BHT Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS **Chemical Abstracts Service** 

Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EC **European Community** 



(B)

Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

**HGWP Halocarbon Global Warming Potential** 

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

**IUCLIDInternational Uniform Chemical Information Database** 

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSHNational Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)



(GB)

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.04.2014 / 0001

Replaces revision of / Version: 15.04.2014 / 0001

Valid from: 15.04.2014 PDF print date: 22.07.2014 Colad Easy2Check

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

## Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.