

This safety data sheet complies with the requirements of: (CLP) Regulation (EC 1272/2008)

Revision Date 15-Sep-2020

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code 104126_101342
Product Name EVERCOAT EZ ULTRA LITE

Contains Styrene

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use All purpose filler. For professional use only.

Uses advised against Uses other than recommended use.

1.3. Details of the supplier of the safety data sheet

<u>Manufacturer</u>	<u>Supplier</u>
ITW Evercoat	
A division of Illinois Tool Works Inc.	
6600 Cornell Road	
Cincinnati, OH 45242 USA	
513-489-7600	

E-mail address:
 Info@evercoat.com

1.4. Emergency telephone number

24-hour emergency phone number - CHEMTREC: 1-800-424-9300 INTERNATIONAL: 1-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION:

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Oral	Category 4 - (H302)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive Toxicity	Category 2 - (H361)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 3 - (H226)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Full text of R-phrases: see section 16

2.2. Label elements

Contains Styrene

**Signal word**

Danger

Statements of hazard

H302 - Harmful if swallowed

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

H226 - Flammable liquid and vapor

Contains Tetrahydrophthalic Anhydride EUH208 - May produce an allergic reaction

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

P330 - Rinse mouth

P501 - Dispose of contents/ container to an approved waste disposal plant

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P280 - Wear protective gloves

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P362 + P364 - Take off all contaminated clothing and wash it before reuse

P280 - Wear eye protection/ face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P405 - Store locked up

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P314 - Get medical advice/attention if you feel unwell

P273 - Avoid release to the environment

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment

P242 - Use only non-sparking tools

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

P370 + P378 - In case of fire: Use .? to extinguish

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to industrial incineration plant

Take precautionary measures against static discharge

Other Information

- Not applicable

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Ground Limestone (Calcium Carbonate)	215-279-6	1317-65-3	30 - 60		Exempt - Annex V
Styrene	202-851-5	100-42-5	10 - 30	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Repr. 2 (H361d) STOT RE 1 (H372) Flam. Liq. 3 (H226)	01-2119457861-32-XXXX
Tetrahydrophthalic Anhydride	201-605-4	85-43-8	0.1 - 1	Eye Dam. 1 (H318) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)	01-2119486679-14-XXXX
Benzenamine, N,N,4-Trimethyl	202-805-4	99-97-8	0.1 - 1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	Exempt - Volume
Paraffin Wax	232-315-6	8002-74-2	0.1 - 1		Exempt - Volume
Isopentane	201-142-8	78-78-4	<0.1	(EUH066) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 1 (H224)	Exempt - Volume
Crystalline Silica (Quartz)	238-878-4	14808-60-7	<0.1		Exempt - Annex V
Phosphoric acid residual	231-633-2	7664-38-2	<0.1	Skin Corr. 1B (H314)	Exempt - Volume

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Skin contact	IF ON SKIN: Wash with soap and water. If symptoms persist, call a physician. Wash contaminated clothing before reuse.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Foam. Use dry chemical.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

Flammable.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures****Personal precautions**

Remove all sources of ignition. Use personal protective equipment as required.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling****Advice on safe handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Avoid breathing vapors or mists.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Take off all contaminated clothing and wash it before reuse. Wash hands and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Strong oxidizing agents

7.3. Specific end use(s)**Specific use(s)**

Automotive Care Product.

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany	
Ground Limestone (Calcium Carbonate) 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	-	-	-	
Styrene 100-42-5	-	TWA: 100 ppm TWA: 430 mg/m ³ STEL: 250 ppm STEL: 1080 mg/m ³	TWA: 23.3 ppm TWA: 100 mg/m ³ TWA: 1000 mg/m ³ STEL: 46.6 ppm STEL: 200 mg/m ³ STEL: 1500 mg/m ³ *	TWA: 20 ppm TWA: 86 mg/m ³ STEL: 40 ppm STEL: 172 mg/m ³	TWA: 20 ppm TWA: 86 mg/m ³	
Paraffin Wax 8002-74-2	-	TWA: 2 mg/m ³ STEL: 6 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	-	
Isopentane 78-78-4	TWA: 1000 ppm TWA: 3000 mg/m ³	TWA: 600 ppm TWA: 1800 mg/m ³ STEL: 1800 ppm STEL: 5400 mg/m ³	TWA: 1000 ppm TWA: 3000 mg/m ³	TWA: 1000 ppm TWA: 3000 mg/m ³	TWA: 1000 ppm TWA: 3000 mg/m ³	
Crystalline Silica (Quartz) 14808-60-7	TWA 0.1 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³	-	
Phosphoric acid residual 7664-38-2	TWA 1 mg/m ³ STEL 2 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 0.2 ppm TWA: 1 mg/m ³ STEL: 0.5 ppm STEL: 2 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 2 mg/m ³	
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark	
Styrene 100-42-5	-	TWA: 20 ppm STEL: 40 ppm	-	TWA: 20 ppm TWA: 86 mg/m ³ STEL: 100 ppm STEL: 430 mg/m ³	Ceiling: 25 ppm Ceiling: 105 mg/m ³ H*	
Paraffin Wax 8002-74-2	-	TWA: 2 mg/m ³	-	TWA: 1 mg/m ³	TWA: 2 mg/m ³	
Isopentane 78-78-4	TWA: 667 ppm TWA: 2000 mg/m ³	TWA: 1000 ppm TWA: 3000 mg/m ³	TWA: 1800 mg/m ³	TWA: 500 ppm TWA: 1500 mg/m ³ STEL: 630 ppm STEL: 1900 mg/m ³	TWA: 500 ppm TWA: 1500 mg/m ³	
Crystalline Silica (Quartz) 14808-60-7	-	TWA: 0.025 mg/m ³	TWA: 0.075 mg/m ³ TWA: 0.75 mg/m ³	TWA: 0.05 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.3 mg/m ³ TWA: 0.1 mg/m ³	
Phosphoric acid residual 7664-38-2	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³	
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland	Slovenia
Ground Limestone (Calcium Carbonate) 1317-65-3	-	-	-	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	
Styrene 100-42-5	TWA: 20 ppm TWA: 85 mg/m ³ STEL 80 ppm STEL 340 mg/m ³	TWA: 20 ppm TWA: 85 mg/m ³ STEL: 40 ppm STEL: 170 mg/m ³	STEL: 100 mg/m ³ TWA: 50 mg/m ³	TWA: 25 ppm TWA: 105 mg/m ³ STEL: 37.5 ppm STEL: 131.25 mg/m ³	TWA: 85 mg/m ³ TWA: 20 ppm STEL: 40 ppm STEL: 170 mg/m ³	TWA: 20 ppm TWA: 86 mg/m ³ STEL: STEL ppm STEL: STEL mg/m ³
Paraffin Wax 8002-74-2	-	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³ STEL: 6 mg/m ³	
Isopentane 78-78-4	TWA: 600 ppm TWA: 1800 mg/m ³ STEL 1200 ppm STEL 3600 mg/m ³	TWA: 600 ppm TWA: 1800 mg/m ³ STEL: 1200 ppm STEL: 3600 mg/m ³	TWA: 3000 mg/m ³	TWA: 250 ppm TWA: 750 mg/m ³ TWA: 40 ppm TWA: 275 mg/m ³ STEL: 312.5 ppm STEL: 937.5 mg/m ³ STEL: 60 ppm STEL: 343.75 mg/m ³	TWA: 1000 ppm STEL: 3000 ppm	TWA: 1000 ppm TWA: 3000 mg/m ³ STEL: STEL mg/m ³ STEL: STEL ppm
Crystalline Silica (Quartz) 14808-60-7	TWA: 0.15 mg/m ³	TWA: 0.15 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.3 mg/m ³ TWA: 0.1 mg/m ³ STEL: 0.9 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	

Phosphoric acid residual 7664-38-2	TWA: 1 mg/m ³ STEL 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	STEL: 2 mg/m ³ TWA: 1 mg/m ³	STEL: 0.3 mg/m ³ TWA: 1 mg/m ³ STEL: 3 mg/m ³	TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³ STEL: STEL mg/m ³
---------------------------------------	--	---	---	--	---	---

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Styrene 100-42-5	-	-	-	400 0.2	600 mg/g Creatinine
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Styrene 100-42-5	-	-	-	1.2	-
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Styrene 100-42-5	-	600	-	-	-

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Use exhaust ventilation to keep airborne concentrations below exposure limits.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Suitable protective clothing. Gloves made of plastic or rubber.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Gray
Odor	Aromatic
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	145 °C / 293 °F	
Flash point	32 °C / 90 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	1.03	
Water solubility	No information available	
Solubility(ies)	Insoluble	
Partition coefficient	1.36	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

9.2. Other information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Applied	43 g/L
Density	5.8
Bulk density	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Excessive heat.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon oxides

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

Inhalation	May cause irritation of respiratory tract.
Eye contact	Irritating to eyes. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. Prolonged contact may cause redness and irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	983.40 mg/kg
ATEmix (dermal)	2,060.20 mg/kg
ATEmix (inhalation-dust/mist)	1.63 mg/l
<u>Unknown acute toxicity</u>	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h
Benzenamine, N,N,4-Trimethyl	= 1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 1400 mg/m ³ (Rat) 4 h

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Central nervous system, Central Vascular System (CVS), Eyes, Liver, Reproductive System, Respiratory system, Skin.
Aspiration hazard:	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Styrene	0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50 1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static	3.3 - 7.4: 48 h Daphnia magna mg/L EC50
Tetrahydrophthalic Anhydride	65.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Oncorhynchus mykiss mg/L LC50 static	-
Benzenamine, N,N,4-Trimethyl	-	42 - 50.5: 96 h Pimephales promelas mg/L LC50 flow-through	-
Isopentane	-	-	2.3: 48 h Daphnia magna mg/L EC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient
Styrene	2.95
Benzenamine, N,N,4-Trimethyl	2.81
Isopentane	3.2 - 3.3

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

Chemical Name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
Styrene	Group I Chemical	High Exposure Concern	-

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
Waste codes / waste designations according to EWC / AVV	No Data Available
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

IMDG

14.1 UN/ID No	UN3269
14.2 Proper shipping name	Polyester Resin Kit
14.3 Hazard Class	3
14.4 Packing Group	III
14.5 Environmental hazard	No information available
14.6 Special Provisions	No information available
14.7 EmS-No	No information available

RID

14.1 UN/ID No	No information available.
14.2 Proper shipping name	No information available
14.3 Hazard Class	No information available.
14.4 Packing Group	No information available.
14.5 Environmental hazard	No information available
14.6 Special Provisions	No information available
14.7 Classification code	No information available

ADR

14.1 UN/ID No	No information available.
14.2 Proper shipping name	No information available
14.3 Hazard Class	No information available.
14.4 Packing Group	No information available.
14.5 Environmental hazard	No information available
14.6 Special Provisions	No information available
14.7 Classification code	No information available

IATA

14.1 UN/ID No	UN3269
14.2 Proper shipping name	Polyester Resin Kit
14.3 Hazard Class	3
14.4 Packing Group	III
14.5 Environmental hazard	No information available
14.6 Special Provisions	No information available

14.7 ERG Code No information available.

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Styrene 100-42-5	RG 84	-
Paraffin Wax 8002-74-2	RG 36	-
Isopentane 78-78-4	RG 84	-
Crystalline Silica (Quartz) 14808-60-7	RG 25	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

- EUH066 - Repeated exposure may cause skin dryness or cracking
- H224 - Extremely flammable liquid and vapor
- H226 - Flammable liquid and vapor
- H301 - Toxic if swallowed
- H304 - May be fatal if swallowed and enters airways
- H311 - Toxic in contact with skin
- H314 - Causes severe skin burns and eye damage
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H318 - Causes serious eye damage
- H319 - Causes serious eye irritation
- H331 - Toxic if inhaled
- H332 - Harmful if inhaled
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H336 - May cause drowsiness or dizziness
- H372 - Causes damage to organs through prolonged or repeated exposure
- H373 - May cause damage to organs through prolonged or repeated exposure
- H411 - Toxic to aquatic life with long lasting effects
- H412 - Harmful to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorization:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Revision Date 15-Sep-2020

Revision Note Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet