

ALLOY PRIMER

Code: PROWSALLOY

Alloy Primer Spray

PROWHEEL Alloy Primer provides excellent adhesion and corrosion prevention. Quick drying. Formulated for refinishing of OEM plated aluminium car wheels.

- Fast drying
- Excellent corrosion protection
- High adhesion on aluminium surfaces
- Supplied with 2 nozzles

Suitable Substrates

Aluminium.

Application Data



Shake aerosol for at least two minutes, after agitator ball is free.



Apply in cross coats from distance of 250mm from object.



Drying time 10-25 minutes.



After use turn aerosol upside down and empty valve.

VOC ✓

500ml



scroll down to continue

ALLOY PRIMER

Code: PROWSALLOY

Technical Data

Chemical base	Special Mix of Resin
VOC content	321 g/500ml
Coverage	1.2m ²
Storage notes	Empty cans 36 month. Relative air humidity of max. 60%)

Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

VOC ✓
500ml

