

### Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 36-8937-9
 Version number:
 11.02

 Revision date:
 10/02/2023
 Supersedes date:
 30/11/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M 51815, 51816, 51818 Fast Cut Plus Extreme

**Product Identification Numbers** 

UU-0089-7239-8 UU-0089-7240-6 UU-0089-7282-8 UU-0095-4165-5 UU-0110-6066-0

7100136343 7100136486 7100136485 7100169681 7100231952

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### **Identified uses**

Automotive.

### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

 Telephone:
 +44 (0)1344 858 000

 E Mail:
 tox.uk@mmm.com

 Website:
 www.3M.com/uk

### 1.4. Emergency telephone number

+44 (0)1344 858 000

### **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

### **CLASSIFICATION:**

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

### SIGNAL WORD

WARNING.

### **Symbols**

GHS08 (Health Hazard) |

### **Pictograms**



Ingredient	CAS Nbr	EC No.	% by Wt
Aluminium oxide	1344-28-1	215-691-6	20 - 30
Water	7732-18-5	231-791-2	10 - 30
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		926-141-6	7 - 13
White mineral oil (petroleum)	8042-47-5	232-455-8	< 10
Glycerol	56-81-5	200-289-5	3 - 7
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		919-446-0	3 - 7
Silicon dioxide	7631-86-9	231-545-4	3 - 7
1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	< 0.05
Sorbitan monooleate, ethoxylated	9005-65-6		< 5
Hydrocarbons, C10 aromatics, <1% naphthalene		918-811-1	< 3
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics		920-114-2	< 3
NJ TSR 54004100000-9915P - PROCESSED CASTOR OIL	Trade Secret		< 3
Oleyl Alcohol	68002-94-8	268-106-1	< 2

### **HAZARD STATEMENTS:**

H373 May cause damage to organs through prolonged or repeated exposure: nervous system.

H412 Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P260A Do not breathe vapours.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### SUPPLEMENTAL INFORMATION:

### **Supplemental Hazard Statements:**

EUH066

Repeated exposure may cause skin dryness or cracking.

4% of the mixture consists of components of unknown acute oral toxicity.

Contains 2% of components with unknown hazards to the aquatic environment.

### 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	0/0	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	10 - 30	Substance not classified as hazardous
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	20 - 30	Substance with a national occupational exposure limit
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6	7 - 13	Asp. Tox. 1, H304 EUH066
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	< 10	Asp. Tox. 1, H304
Silicon dioxide	(CAS-No.) 7631-86-9 (EC-No.) 231-545-4	3 - 7	Substance with a national occupational exposure limit
Glycerol	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	3 - 7	Substance with a national occupational exposure limit
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC-No.) 919-446-0	3 - 7	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 STOT RE 1, H372
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315

			Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 1, H410,M=1
Sorbitan monooleate, ethoxylated	(CAS-No.) 9005-65-6	< 5	Substance not classified as hazardous
NJ TSR 54004100000-9915P - PROCESSED CASTOR OIL	Trade Secret	< 3	Substance not classified as hazardous
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	(EC-No.) 920-114-2	< 3	Asp. Tox. 1, H304 EUH066
Hydrocarbons, C10 aromatics, <1% naphthalene	(EC-No.) 918-811-1	< 3	Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 Aquatic Chronic 2, H411
Oleyl Alcohol	(CAS-No.) 68002-94-8 (EC-No.) 268-106-1	< 2	Substance not classified as hazardous

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

### **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.05%) Skin Sens. 1, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Toxic by eye contact. Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

### **SECTION 5: Fire-fighting measures**

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbons.During combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial/occupational use only. Not for consumer sale or use. Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient Aluminium oxide	CAS Nbr 1344-28-1	<b>Agency</b> UK HSC	Limit type TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	Additional comments
Glycerol	56-81-5	UK HSC	TWA(as mist):10 mg/m3	
DUST, INERT OR NUISANCE	7631-86-9	UK HSC	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	<b>Breakthrough Time</b>
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:EmulsionColourWhiteOdorPine, Oily

No data available. **Odour threshold** Melting point/freezing point Not applicable. No data available. Boiling point/boiling range Flammability (solid, gas) Not applicable. Flammable Limits(LEL) No data available. Flammable Limits(UEL) No data available. Flash point No data available. **Autoignition temperature** No data available.

Autoignition temperatureNo data available.Decomposition temperatureNo data available.

pH 7.5 9 Units not available or not applicable. [Details:@20 C

(+/-1 C)

Kinematic Viscosity17,319 - 60,870 mm²/secWater solubilityNo data available.Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNo data available.

**Density** 1.15 g/ml

**Relative density** 1.15 [Ref Std: WATER=1]

**Relative Vapour Density**No data available.

#### 9.2. Other information

9.2.2 Other safety characteristics

**EU Volatile Organic Compounds No data available. Evaporation rate**Not applicable.

Percent volatile 20 %

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

High shear and high temperature conditions Sparks and/or flames.

### 10.5 Incompatible materials

Alkali and alkaline earth metals. Strong oxidising agents.

### 10.6 Hazardous decomposition products

### **Substance**

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

### **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause additional health effects (see below).

### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

### **Eve contact**

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Additional Health Effects:**

#### Prolonged or repeated exposure may cause target organ effects:

Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation- Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
Glycerol	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerol	Ingestion	Rat	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Dermal	Not available	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
Sorbitan monooleate, ethoxylated	Ingestion	Rat	LD50 20,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation- Vapour	Professio nal judgeme	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 454 mg/kg

 $\overline{ATE}$  = acute toxicity estimate

### Skin Corrosion/Irritation

Skiii Cui i usiuii/ii i itatiuii			
Name	Species	Value	
Aluminium oxide	Rabbit	No significant irritation	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation	
White mineral oil (petroleum)	Rabbit	No significant irritation	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	Minimal irritation
Silicon dioxide	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Minimal irritation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	No significant irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminium oxide	Rabbit	No significant irritation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	No significant irritation
Silicon dioxide	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Mild irritant
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

#### Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Guinea pig	Not classified
Silicon dioxide	Human and animal	Not classified
Glycerol	Guinea pig	Not classified
Sorbitan monooleate, ethoxylated	Guinea pig	Not classified
Hydrocarbons, C10 aromatics, <1% naphthalene	Guinea pig	Not classified
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
1,2-benzisothiazol-3(2H)-one	Guinea pig	Sensitising

**Respiratory Sensitisation**For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminium oxide	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Silicon dioxide	In Vitro	Not mutagenic
Sorbitan monooleate, ethoxylated	In Vitro	Not mutagenic
Hydrocarbons, C10 aromatics, <1% naphthalene	In Vitro	Not mutagenic
Hydrocarbons, C10 aromatics, <1% naphthalene	In vivo	Not mutagenic
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic

1,2-benzisothiazol-3(2H)-one In Vitro	Some positive data exist, but the data are not sufficient for classification
---------------------------------------	--

Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%	Not	Not	Not carcinogenic
aromatics	specified.	available	
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerol	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Sorbitan monooleate, ethoxylated	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

### **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Glycerol	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation

Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	gestation into lactation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

### Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2-benzisothiazol-3(2H)- one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Glycerol	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerol	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Sorbitan monooleate, ethoxylated	Ingestion	heart   endocrine system   gastrointestinal tract   bone, teeth, nails,	Not classified	Rat	NOAEL 4,132 mg/kg/day	90 days

1,2-benzisothiazol-3(2H)- one	Ingestion	and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system liver   hematopoietic system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	heart   endocrine system   nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

**Aspiration Hazard** 

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Aspiration hazard
Hydrocarbons, C10 aromatics, <1% naphthalene	Aspiration hazard
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

### **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C11-C14, n- alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n- alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l

Hydrocarbons,	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
C11-C14, n-	920-141-0	water frea	Experimental	46 Hours	ELSU	71,000 mg/1
alkanes, isoalkanes,						
cyclics, <2%						
aromatics						
Hydrocarbons,	926-141-6	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
C11-C14, n-			1			
alkanes, isoalkanes,						
cyclics, <2%						
aromatics						
White mineral oil	8042-47-5	Water flea	Analogous	48 hours	EL50	>100 mg/l
(petroleum)			Compound			
White mineral oil	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
(petroleum)						
White mineral oil	8042-47-5	Green algae	Analogous	72 hours	NOEL	100 mg/l
(petroleum)			Compound			
White mineral oil	8042-47-5	Water flea	Analogous	21 days	NOEL	>100 mg/l
(petroleum)			Compound			
Glycerol	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
~ .				0.01		
Glycerol	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
~ .						1.055 //
Glycerol	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
**	0.0.0.0.0					
Hydrocarbons, C9-	919-446-0	Green algae	Estimated	72 hours	EL50	4.1 mg/l
C12, n-alkanes,						
isoalkanes, cyclics,						
aromatics (2-25%)	010 446 0	D:1 4	F ( 1	061	11.50	10 20 //
Hydrocarbons, C9-	919-446-0	Rainbow trout	Estimated	96 hours	LL50	10 - 30 mg/l
C12, n-alkanes, isoalkanes, cyclics,						
aromatics (2-25%)						
Hydrocarbons, C9-	919-446-0	Water flea	Estimated	48 hours	EL50	10 - 22 mg/l
C12, n-alkanes,	919-440-0	water fiea	Estimated	46 110015	ELSO	10 - 22 mg/1
isoalkanes, cyclics,						
aromatics (2-25%)						
	919-446-0	Green algae	Estimated	72 hours	NOEL	0.76 mg/l
C12, n-alkanes,		oreen argue	25tmateu	72 110 415	1,022	0.70 mg/1
isoalkanes, cyclics,						
aromatics (2-25%)						
Hydrocarbons, C9-	919-446-0	Water flea	Estimated	21 days	EC10	0.316 mg/l
C12, n-alkanes,						
isoalkanes, cyclics,						
aromatics (2-25%)						
Silicon dioxide	7631-86-9	N/A	Data not available	N/A	N/A	N/A
			or insufficient for			
			classification			
1,2-benzisothiazol-	2634-33-5	Green algae	Experimental	72 hours	ErC50	0.11 mg/l
3(2H)-one						
1,2-benzisothiazol-	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
3(2H)-one						
1,2-benzisothiazol-	2634-33-5	Sheepshead	Experimental	96 hours	LC50	16.7 mg/l
3(2H)-one		Minnow				
1,2-benzisothiazol-	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
3(2H)-one						
1,2-benzisothiazol-	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
3(2H)-one		1	<del> </del>			
1,2-benzisothiazol-	2634-33-5	Activated sludge	Experimental	3 hours	EC50	12.8 mg/l
3(2H)-one		<u> </u>	<u> </u>	1	1	100
1,2-benzisothiazol-	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight
3(2H)-one			<u> </u>	1	la case	
1,2-benzisothiazol-	2634-33-5	Cabbage	Experimental	14 days	EC50	200 mg/kg (Dry Weight)
3(2H)-one	0.04.00.5	n	<u></u>		V 050	1106 7 7 77
1,2-benzisothiazol-	2634-33-5	Redworm	Experimental	14 days	LC50	>410.6 mg/kg (Dry Weight)
3(2H)-one	2624 22 5	G 71 : 1	  r · · ·	20.1	IEG50	5011 5 # OD WY 1 10
1,2-benzisothiazol-	2634-33-5	Soil microbes	Experimental	28 days	EC50	>811.5 mg/kg (Dry Weight)
3(2H)-one		1	1	<u> </u>	1	

Sorbitan	9005-65-6	Copepod	Analogous	48 hours	LL50	>10,000 mg/l
monooleate,	9003-03-0	Сорероц	Compound	46 1100115	LLSU	710,000 mg/1
ethoxylated			Compound			
Sorbitan	9005-65-6	Green algae	Analogous	72 hours	EL50	58.84 mg/l
monooleate,	9003-03-0	Green algae	Compound	/2 nours	ELSO	36.64 Hig/I
			Compound			
ethoxylated	0005 (5 (	7.1 5.1	A 1	061	1.050	> 100 //
Sorbitan	9005-65-6	Zebra Fish	Analogous	96 hours	LC50	>100 mg/l
monooleate,			Compound			
ethoxylated					77.0	1000
Sorbitan	9005-65-6	Green algae	Analogous	72 hours	EC10	19.05 mg/l
monooleate,			Compound			
ethoxylated						
Sorbitan	9005-65-6	Water flea	Analogous	21 days	NOEL	10 mg/l
monooleate,			Compound			
ethoxylated						
Hydrocarbons, C10	918-811-1	Green algae	Estimated	72 hours	EL50	3 mg/l
aromatics, <1%						
naphthalene						
Hydrocarbons, C10	918-811-1	Rainbow trout	Estimated	96 hours	LL50	5 mg/l
aromatics, <1%						
naphthalene						
Hydrocarbons, C10	918-811-1	Water flea	Estimated	48 hours	EL50	10 mg/l
aromatics, <1%						
naphthalene						
Hydrocarbons, C10	918-811-1	Green algae	Estimated	72 hours	NOEL	1 mg/l
aromatics, <1%	710 011 1	or con argue	Loumatou	72 110 415	11022	1g, 1
naphthalene						
Hydrocarbons,	920-114-2	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
C14-C19,	720 114 2	renvated staage	Estimated	3 nours	Leso	2 100 mg/1
isoalkanes, cyclics,						
<2% aromatics						
Hydrocarbons,	920-114-2	Fish	Estimated	96 hours	LL50	>1,028 mg/l
C14-C19,	720-114-2	1 1511	Listimated	70 Hours	LLSO	- 1,020 mg/1
isoalkanes, cyclics,						
<2% aromatics						
Hydrocarbons,	920-114-2	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
C14-C19,	920-114-2	Green aigae	Estimateu	/2 Hours	ELSO	71,000 mg/1
isoalkanes, cyclics,						
<2% aromatics						
	020 114 2	W-4 £1	D-timet 4	40 1	EL 50	> 1 000/I
Hydrocarbons,	920-114-2	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
C14-C19,						
isoalkanes, cyclics,						
<2% aromatics	020 114 2		E di di	72.1	NOT	1,000 //
Hydrocarbons,	920-114-2	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
C14-C19,						
isoalkanes, cyclics,						
<2% aromatics			<u> </u>			
Hydrocarbons,	920-114-2	Water flea	Estimated	21 days	NOEL	5 mg/l
C14-C19,						
isoalkanes, cyclics,						
<2% aromatics						
Oleyl Alcohol	68002-94-8	Water flea	Experimental	48 hours	EC50	70 mg/l

### 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium oxide	1344-28-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C14, n- alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 %BOD/ThOD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2

Glycerol	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Estimated Biodegradation	28 days	BOD	75 %BOD/ThOD	OECD 301F - Manometric respirometry
Silicon dioxide	7631-86-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Aquatic Inherent Biodegrad.	34 days	Dissolv. Organic Carbon Deplet	17 %removal of DOC	OECD 302A - Modified SCAS Test
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	80 %removal of DOC	OECD 303A - Simulated Aerobic
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Biodegradation		Half-life (t 1/2)	4 hours (t 1/2)	
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Hydrolysis		Hydrolytic half-life	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
Sorbitan monooleate, ethoxylated	9005-65-6	Experimental Biodegradation	28 days	CO2 evolution	61 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Experimental Biodegradation	28 days	BOD	49.6 %BOD/COD	OECD 301F - Manometric respirometry
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Estimated Biodegradation	28 days	BOD	82 %BOD/ThOD	OECD 301F - Manometric respirometry
Oleyl Alcohol	68002-94-8	Experimental Biodegradation	28 days	BOD	87 %BOD/ThOD	OECD 301D - Closed bottle test

### 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C14, n- alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental BCF - Fish	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol- 3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd
Sorbitan monooleate, ethoxylated	9005-65-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C14-C19,	920-114-2	Data not available or insufficient for	N/A	N/A	N/A	N/A

### 3M 51815, 51816, 51818 Fast Cut Plus Extreme

isoalkanes, cyclics,		classification				
<2% aromatics						
Oleyl Alcohol	68002-94-8	Data not available	N/A	N/A	N/A	N/A
		or insufficient for				
		classification				

### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Glycerol	56-81-5	Estimated Mobility	Koc	<1 l/kg	Episuite <sup>TM</sup>
		in Soil			
1,2-benzisothiazol-	2634-33-5	Experimental	Koc	9.33 l/kg	OECD 121 Estim. of Koc by
3(2H)-one		Mobility in Soil			HPLC

### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

120109\* Machining emulsions and solutions free of halogens

## SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.

14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	nicity	

Ingredient	CAS Nbr	<b>Classification</b>	Regulation
Silicon dioxide	7631-86-9	Gr. 3: Not classifiable	International Agency for Research on Cancer

### Global inventory status

Contact 3M for more information.

### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances Identifier(s)		Qualifying quantity (tonnes) for the application of		
		Lower-tier requirements	Upper-tier requirements	
1,2-benzisothiazol-3(2H)-one	2634-33-5	100	200	

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

### **SECTION 16: Other information**

#### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

- GB Section 02: CLP Ingredient table information was added.
- GB Section 02: Other hazards phrase information was added.
- GB Section 04: First Aid Symptoms and Effects (GB CLP) information was added.
- GB Section 04: Information on toxicological effects information was added.
- GB Section 12: Classification Warning information was added.
- GB Section 15: Carcinogenicity information information was added.
- GB Section 15: Chemical Safety Assessment information was added.
- GBSDS Section 14 Transport in bulk Main Heading information was added.
- GBSDS Section 14 UN Number information was added.

Professional Use of Coatings: Section 16: Annex information was deleted.

Contains statement for sensitizers information was deleted.

- Label: CLP Percent Unknown information was deleted.
- Label: CLP Precautionary Disposal information was added.
- Label: CLP Precautionary General information was added.
- Label: CLP Precautionary Prevention information was added.
- Section 02: Label Elements: GB Percent Unknown information was added.

List of sensitizers information was deleted.

- Section 2: Other hazards phrase information was deleted.
- Section 3: Composition/Information of ingredients table information was added.
- Section 3: Composition/Information of ingredients table information was deleted.
- Section 03: SCL table information was added.
- Section 03: SCL table information was deleted
- Section 04: First Aid Symptoms and Effects (CLP) information was deleted.
- Section 04: Information on toxicological effects information was deleted.
- Section 5: Fire Advice for fire fighters information information was modified.
- Section 5: Fire Extinguishing media information information was modified.
- Section 8: 8.2. Exposure controls information information was deleted.
- Section 8: 8.2.3. Environmental exposure controls information information was deleted.
- Section 8: Occupational exposure limit table information was modified.
- Section 9: Flash point information information was modified.

### 3M 51815, 51816, 51818 Fast Cut Plus Extreme

- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Classification disclaimer information was deleted.
- Section 11: GB Classification disclaimer information was added.
- Section 11: GB No endocrine disruptor information available warning information was added.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Health Effects Skin information information was modified.
- Section 11: No endocrine disruptor information available warning information was deleted.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 12: 12.6. Endocrine Disrupting Properties information was deleted.
- Section 12: 12.6. Other adverse effects information was added.
- Section 12: 12.7. Other adverse effects information was deleted.
- Section 12: Classification Warning information was deleted.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Prints No Data if Adverse effects information is not present information was deleted.
- Section 12: No endocrine disruptor information available warning information was added.
- Section 12: No endocrine disruptor information available warning information was deleted.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 14 Marine transport in bulk according to IMO instruments Main Heading information was deleted.
- Section 14 UN Number information was deleted.
- Section 15: Chemical Safety Assessment information was deleted.
- Section 15: Seveso Substance Text information was added.
- Section 15: Seveso Substance Text information was deleted.
- Annex: Prediction of exposure statement information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

- Section 16: Web address information was added.
- Section 16: Web address information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.