

Technical Data Sheet

General

Article number: 9068

Description: Colad Ceramic Protection



Description

The silicon-free, highly durable coating with 9H hardness, for a strong long-lasting protection and an easy-to-clean surface.

Colad Ceramic Protection is suitable to treat any kind of metal, plastic, or painted surfaces. The silicon-free ceramic coating with 9H hardness offers protection against weather influences, acid rain, scratches, chemicals, dirt, UV radiation, oxidation, and corrosion. The product can be used inside the body shop because it is silicon-free, preventing contamination of paint applications. It creates a thin and resistant layer of ceramic protection on the treated surface. This layer protects the surface against environmental conditions, insect marks, bird droppings, tree resins, chemicals, dirt, acid rain, UV radiation, and increases the protection against minor scratches and stone chips. It maintains a shine longer and makes the surface much easier to clean, thanks to its excellent water repellency. The product is easy to apply with the Microsuede Applicator Pad included, and you will never miss a spot since the product lightens up when exposed to any UV light, thanks to our UV Control Technology.

Once well applied, one layer will protect the surface for up to 2 years or 50 washing cycles under normal conditions.

Features:

- Closed layer surface protection
- 9H hardness
- UV light application control
- Scratch resistant
- Hydrophobic effect (water-repellency)
- Silicon free
- Heat resistant up to 1000C
- Oxidation and corrosion resistant
- Weather and UV resistant
- One 38ml bottle is enough for one large vehicle (SUV) or up to two small vehicles

Benefits:

- Included applicator for fast and smooth application
- Never miss a spot due to the UV light application control
- Can be used on any painted surface
- Eases the cleaning of the treated surface
- Protects against weather influences, dirt, oxidation and corrosion
- Protects up to 2 years or 50 washing cycles

Remark: only apply with the Microsuede Applicator Pad provided. Make sure not to dry the sponge and re-use it. That will create scratches on the surface. You should wear gloves when applying the product, and if you are using a UV light, you should wear long sleeves, UV goggles and gloves.

Note: use any type of UV light device to check whether you have covered the complete surface.

Technical specifications

Colour: Transparent

Storage advise: from +5°C to +30°C

Shelf life: 1 year when kept at a temperature between 5°C – 30°C. See expiry date on the can (after opening bottle, 1 week)

Drying time: 4 hours for touch cure, 7 days for wash cure, 28 days for full cure

Packaging: Box containing 1 x 38 ml aluminium bottle + Microsuede Applicator Pad+ Application manual

Packing: 12 boxes in display carton

Related products

Colad Surface Preparation

Art.no. 9067

Colad Microsuede Applicator Pad

Art.no. 9069

Colad Microfiber Polishing Cloths

Art.no. 8800

Published by:

EMM International BV

Bohemestraat 19, 8028 SB Zwolle, The Netherlands

www.emm.com

T +31(0)38 467 66 00

www.colad.co

Disclaimer:

Technical Data Sheet and Material Safety Data Sheet

It is the responsibility of the user to read, understand and apply the information of the TDS. It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn.

The repairs should always be done in accordance with the OEM rules and specifications.

All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.