

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

#### **SECTION 1:** Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product identifier	: S351
Product name	: SYROX TINT REDDISH YELLOW
Product type	: Liquid.
Other means of identification	: 1250088644
Date of issue/ Date of revision	: 30 April 2024
Version	: 1.06
Date of previous issue	: 4 March 2024

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	: Coating component.	
Uses advised against	: Not for sale to or use by consun	ners.

#### 1.3 Details of the supplier of the safety data sheet

Axalta Coating Systems Ger	many GmbH & Co. KG
Christbusch 25	
DE 42285 Wuppertal	
+49 (0)202 529-0	
e-mail address of person responsible for this SDS	: sds-competence@axalta.com

#### 1.4 Emergency telephone number

<u>Supplier</u>	
Telephone number	: +(44)-870-8200418
Hours of operation	:

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### **Classification according to UK CLP/GHS**

Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

# **SECTION 2: Hazards identification**

Hazard pictograms	:	<b>^</b>
Signal word	:	Warning
Hazard statements	:	H319 - Causes serious eye irritation.
Precautionary statements		
Prevention	:	P280 - Wear eye or face protection.
Response	:	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	EUH208 - Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

# **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Туре
(2-methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	[2]
1-pentanol	REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1	<2.5	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	≤0.3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.01	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	[1]

# SPROX TIME REDDISH VELLOW SECTION 3: Composition/information on ingredients (M=10) Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.</li> </ul>
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

# Over-exposure signs/symptomsEye contact: Adverse symptoms may include the following:<br/>pain or irritation<br/>watering<br/>rednessInhalation: No specific data.Skin contact: No specific data.

Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed.<br/>The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue/Date of revision : 4/30/2024 Date of previous is	ssue : 3/4/2024 Versio	<b>1</b> :1.06	3/16
--	------------------------	----------------	------

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 SYROX TINT REDDISH YELLOW

# SECTION 4: First aid measures

**Specific treatments** : No specific treatment.

#### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray.
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	ron	the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

# SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

#### 6.1 Personal precautions, protective equipment and emergency procedures

err i ereenar preedaarene, pre		stre equipment and entregence preceduree
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used.

# **SECTION 7: Handling and storage**

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
(2-methoxymethylethoxy)propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 308 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
2-dimethylaminoethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 22 mg/m <sup>3</sup> 15 minutes. STEL: 6 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 7.4 mg/m <sup>3</sup> 8 hours.

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring	:	Reference should be made to appropriate monitoring standards. Reference to
procedures		national guidance documents for methods for the determination of hazardous
-		substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
(2-methoxymethylethoxy)propanol	DNEL	Long term Dermal	65 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	50.4 ppm	Workers	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m <sup>3</sup>		Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic

	DNEL	Long term Dermal	283 mg/kg	Workers	Systemic
	DINEL		bw/day	VVUINEIS	Systemic
	DNEL	Long term	308 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	_		
1-pentanol	DNEL	Long term	20 ppm	Workers	Systemic
		Inhalation			-
	DNEL	Long term Oral	12.5 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	13 mg/m <sup>3</sup>	General	Local
		Inhalation		population	
	DNEL	Long term	73.16 mg/	Workers	Local
		Inhalation	m³		
	DNEL	Short term	218 mg/m <sup>3</sup>	General	Local
		Inhalation		population	
	DNEL	Short term	292 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
2-dimethylaminoethanol	DNEL	Short term Dermal	100 µg/cm²	Workers	Local
	DNEL	Long term Oral	0.148 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.25 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	0.43755	General	Systemic
		Inhalation	mg/m³	population	
	DNEL	Short term Dermal	1.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	1.76 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Long term	1.76 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	0.11		
	DNEL	Short term	5.28 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			-
	DNEL	Short term	13.53 mg/	Workers	Local
		Inhalation	m³		
1,2-benzisothiazol-3(2H)-one	DNEL	Long term	6.81 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term Dermal	0.345 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.2 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Long term	6.81 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
(2-methoxymethylethoxy)propanol	Marine water	1.9 mg/l	-
	Fresh water	19 mg/l	-
	Fresh water sediment	70.2 mg/l	-
	Secondary Poisoning	190 mg/l	-
	Sewage Treatment	4168 mg/l	-
	Plant		
	Marine water sediment	7.02 mg/kg	-
	Soil	2.74 mg/kg	-
1-pentanol	Fresh water	0.12 mg/l	-
	Marine water	0.012 mg/l	-
	Secondary Poisoning	1.2 mg/l	-
	Fresh water sediment	0.496 mg/kg	-
	Marine water sediment	0.0496 mg/kg	-
	Sewage Treatment	37 mg/l	-
	Plant	-	
	Soil	1.068 mg/kg	-
e of issue/Date of revision : 4/30/2024	4 Date of previous issue	: 3/4/2024	Version : 1.06 6

## **SECTION 8: Exposure controls/personal protection**

control of the controls/personal protection						
2-dimethylaminoethanol	Fresh water	0.066 mg/l	-			
	Marine water	0.007 mg/l	-			
	Soil	0.01 mg/kg	-			
	Sewage Treatment	10 mg/l	-			
	Plant	-				
1,2-benzisothiazol-3(2H)-one	Fresh water	4.03 µg/l	-			
	Marine water	0.403 µg/l	-			
	Sewage Treatment	1.03 mg/l	-			
	Plant	-				
	Fresh water sediment	49.9 µg/kg dwt	-			
	Marine water sediment	4.99 µg/kg dwt	-			
	Soil	3 mg/kg	-			

8.2 Exposure controls Appropriate engineering controls	: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
Individual protection meas	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
combination of chemicals The breakthrough time n The instructions and info replacement must be foll Gloves should be replace Always ensure that glove The performance or effe maintenance. Barrier creams may help occurred.	nust be greater than the end use time of the product. rmation provided by the glove manufacturer on use, storage, maintenance and owed. ed regularly and if there is any sign of damage to the glove material. is are free from defects and that they are stored and used correctly. ctiveness of the glove may be reduced by physical/chemical damage and poor to protect the exposed areas of the skin but should not be applied once exposure has
Gloves	<ul> <li>Duration / breakthrough time: &lt;1 hour, Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374) Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)</li> <li>The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Expert judgment</li> <li>The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.</li> </ul>
Body protection	<ul> <li>Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

# **SECTION 8: Exposure controls/personal protection**

-	· ·
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

# 9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Orange.
Odour	:	Not available.
Odour threshold	:	Not available.
Melting point/freezing point	:	Technically not possible to measure
Initial boiling point and boiling range	:	100 to 100.1°C (212 to 212.2°F)
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
		Not available.
Flash point		Closed cup: 99°C (210.2°F) [Product does not sustain combustion.]
Auto-ignition temperature	:	207°C (404.6°F)
Decomposition temperature	:	Not applicable.
рН	:	7 to 9
Viscosity		Not available.
VISCOSILY		
Solubility(ies)	:	
•	:	Result
Solubility(ies)	:	Soluble
Solubility(ies) Media cold water Solubility in water	:	
Solubility(ies) Media cold water		Soluble
Solubility(ies) Media cold water Solubility in water	:	Soluble       Not available.       Yes.       Not applicable.
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure	::	Soluble       Not available.       Yes.       Not applicable.       1.9 kPa (14.4 mm Hg)
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density	::	Soluble       Not available.       Yes.       Not applicable.       1.9 kPa (14.4 mm Hg)       Not available.
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density	::	Soluble       Not available.       Yes.       Not applicable.       1.9 kPa (14.4 mm Hg)
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density Vapour density	: : : : :	Soluble       Not available.       Yes.       Not applicable.       1.9 kPa (14.4 mm Hg)       Not available.
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density Vapour density Explosive properties		Soluble         Not available.         Yes.         Not applicable.         1.9 kPa (14.4 mm Hg)         Not available.         1.038 g/cm³
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density Vapour density Explosive properties Oxidising properties		Soluble         Not available.         Yes.         Not applicable.         1.9 kPa (14.4 mm Hg)         Not available.         1.038 g/cm³         Not available.         Not available.         Not available.         Not available.         Not available.
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density Vapour density Explosive properties Oxidising properties Weight volatiles		Soluble         Not available.         Yes.         Not applicable.         1.9 kPa (14.4 mm Hg)         Not available.         1.038 g/cm³         Not available.         Not available.
Solubility(ies) Media cold water Solubility in water Miscible with water Partition coefficient: n-octanol/ water Vapour pressure Relative density Density Vapour density Explosive properties Oxidising properties		Soluble         Not available.         Yes.         Not applicable.         1.9 kPa (14.4 mm Hg)         Not available.         1.038 g/cm³         Not available.         Not available.         Not available.         Not available.         Not available.

#### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

8/16

# **SECTION 9: Physical and chemical properties**

Further information Not available.

#### 9.2.2 Other safety characteristics Miscible with water : Yes.

Further information Not available.

room temperature (=20°C)

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.			
	Not applicable			

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(2-methoxymethylethoxy) propanol	LD50 Dermal	Rabbit	9510 mg/kg	-
1-pentanol	LD50 Dermal LD50 Oral	Rabbit - Male Rat	2860 mg/kg 3030 mg/kg	-
2-dimethylaminoethanol	LC50 Inhalation Gas. LD50 Oral	Rat Rat	1641 ppm 2 g/kg	4 hours -
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0.21 mg/l	4 hours
	LD50 Oral	Rat	1020 mg/kg	-

9/16

# **SECTION 11: Toxicological information**

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	N/A	N/A	579771.7	847.2	N/A
(2-methoxymethylethoxy)propanol	N/A	9510	N/A	N/A	N/A
1-pentanol	3030	2860	N/A	11	N/A
2-dimethylaminoethanol	2000	1100	1641	N/A	N/A
1,2-benzisothiazol-3(2H)-one	1020	N/A	N/A	N/A	0.21

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
	Skin - Severe irritant	Rabbit	-	mg 24 hours 3200 mg	-
2-dimethylaminoethanol	Eyes - Oedema of the conjunctivae	Rabbit	3	-	-
	Eyes - Severe irritant	Rabbit	-	5 uL	-
	Skin - Mild irritant	Rabbit	-	445 mg	-
1,2-benzisothiazol-3(2H)-one	Eyes - Severe irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Human	-	48 hours 5 %	-

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitising

#### **Mutagenicity**

#### **Carcinogenicity**

#### **Reproductive toxicity**

#### **Teratogenicity**

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-pentanol	Category 3	-	Respiratory tract irritation
2-dimethylaminoethanol	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

# Information on likely routes : Not available.

of exposure

Potential acute health effects		
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards	•
Skin contact	: No known significant effects or critical hazards	-

Date of issue/Date of revision

# **SECTION 11: Toxicological information**

```
Ingestion
```

: No known significant effects or critical hazards.

the following:

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Other information

: Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Acute LC50 180 ppm Marine water	Fish - Inland silverside - Menidia beryllina	96 hours
	Chronic EC10 0.059 mg/l	Daphnia	21 days
	Chronic NOEC 10 mg/l	Fish	35 days
2-dimethylaminoethanol	Acute EC50 98.37 mg/l	Daphnia	48 hours
-	Acute LC50 146.63 mg/l Fresh water	Fish	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.11 mg/l	Algae	72 hours
	Acute EC50 97 ppb Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia	48 hours
	Acute LC50 167 ppb Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.0403 mg/l	Algae	72 hours

Conclusion/Summary

: Not available.

#### 12.2 Persistence and degradability

# **SECTION 12: Ecological information**

Product/ingredient name	Test	Result	Dose	Inoculum
1-pentanol	OECD 310	100 % - Readily - 18 days	-	-
	Ready			
	Biodegradability -			
	CO2 in Sealed			
	Vessels			
	(Headspace			
	Test)			
2-dimethylaminoethanol	OECD 302C	60.5 % - Readily - 28 days	-	-
	Inherent			
	Biodegradability:			
	Modified MITI			
	Test (II)			
1,2-benzisothiazol-3(2H)-one	9 -	70 % - Readily - 28 days	-	-
Conclusion/Summary	: Not available.			

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-pentanol	-	-	Readily
2-dimethylaminoethanol	-	-	Readily
1,2-benzisothiazol-3(2H)-one	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(2-methoxymethylethoxy) propanol	0.004	-	Low
1-pentanol 2-dimethylaminoethanol	1.51 -0.55	-	Low Low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Other adverse effects** : No known significant effects or critical hazards.

# SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
Waste catalogue	

# **SECTION 13: Disposal considerations**

	Waste code	Waste designation		
08 01 19* aqueous suspensions containing paint or varnish containing organic solv hazardous substances		aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances		
<u>P</u>	ackaging			
Methods of disposal		<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>		
Type of packaging Waste catalogue		Waste catalogue		
		15.01.10* packaging containing residues of or contaminated by		

	hazardous substances
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA		
14.1 UN number	Not regulated.	9003	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C ( (2-methoxymethylethoxy) propanol, 1-pentanol)	-	-		
14.3 Transport hazard class(es)	-	9	-	-		
14.4 Packing group	-	-	-	-		
14.5 Environmental hazards	No.	No.	No.	No.		

**Additional information** ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to IMO instruments

# SECTION 15: Regulatory information

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

#### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### National regulations

	Product/ingredient name	List name	Name on list	Classification	Notes	
--	-------------------------	-----------	--------------	----------------	-------	--

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

15.2 Chemical safety	:	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RBN = REACH Registration Number</li> </ul>
	RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Classification	Justification	
Eye Irrit. 2, H319	Calculation method	

#### Full text of abbreviated H statements

# **SECTION 16: Other information**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

#### Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
Date of issue/ Date or	f : 4/30/2024	

revision		
Version	:	1.06
Date of previous issue	:	3/4/2024

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

**SECTION 16: Other information**