

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

: S608
: SYROX TINT COARSE SILVER
: Liquid.
: 1250088691
: 30 April 2024
: 1.07
: 24 April 2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	: Coating component.
Uses advised against	: Not for sale to or use by consumers.

1.3 Details of the supplier of the safety data sheet

Axalta Coating Systems Ger	many GmbH & Co. KG
Christbusch 25	
DE 42285 Wuppertal	
+49 (0)202 529-0	
e-mail address of person responsible for this SDS	: sds-competence@axalta.com

1.4 Emergency telephone number

<u>Supplier</u>	
Telephone number	: +(44)-870-8200418
Hours of operation	:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Eye Dam. 1, H318 Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown : Contains 4.4% of components with unknown hazards to the aquatic environment **ecotoxicity**

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 SYROX TINT COARSE SILVER

SECTION 2: Hazards identification

Hazard pictograms	
Signal word	: Danger
Contains	: 1-pentanol
Hazard statements	: H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: P280 - Wear eye or face protection. P273 - Avoid release to the environment.
Response	 P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: EUH208 - Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

Mixture			
Identifiers	%	Classification	Туре
REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1	<10	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2	≤5	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5	≤5	Flam. Sol. 1, H228	[1] [2]
REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1] [2]
	Identifiers REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1 REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0	Identifiers%REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1<10	Identifiers % Classification REACH #: <10

SECTION 3: Composit			STOT SE 3, H335	
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24 EC: 213-048-4 CAS: 919-30-2 Index: 612-108-00-0	≤0.2	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8	≤0.2	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the

concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid	t measures
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
4.2 Most important sympton Over-exposure signs/symp	ns and effects, both acute and delayed
	: Adverse symptoms may include the following:
Eye contact	pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	 Adverse symptoms may include the following: stomach pains
4.3 Indication of any immed Notes to physician	iate medical attention and special treatment needed : Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising t	from the substance or mixture
Hazards from the substance or mixture	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	: Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision

SECTION 6: Accidental release measures

6.2 Environmental	: Do not allow to enter drains or watercourses. If the product contaminates lakes,
precautions	rivers, or sewers, inform the appropriate authorities in accordance with local
	regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 560 mg/m ³ 15 minutes.
	STEL: 150 ppm 15 minutes.
	TWA: 375 mg/m ³ 8 hours.
	TWA: 100 ppm 8 hours.
Aluminium powder (stabilized)	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 4 mg/m ³ 8 hours. Form: respirable dust
	TWA: 10 mg/m ³ 8 hours. Form: inhalable dust
2-dimethylaminoethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	STEL: 22 mg/m ³ 15 minutes.
	STEL: 6 ppm 15 minutes.
	TWA: 2 ppm 8 hours.
	TWA: 7.4 mg/m ³ 8 hours.
triethylamine	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 17 mg/m ³ 15 minutes.
	TWA: 2 ppm 8 hours.
	TWA: 8 mg/m ³ 8 hours.
	STEL: 4 ppm 15 minutes.

Biological exposure indices

No exposure indices known.

Recommended monitoring	:	Reference should be made to appropriate monitoring standards. Reference to
procedures		national guidance documents for methods for the determination of hazardous
		substances will also be required.

DNELs/DMELs

DNEL DNEL DNEL DNEL	Long term Inhalation Long term Oral Long term Inhalation	20 ppm 12.5 mg/ kg bw/day 13 mg/m ³	Workers General population	Systemic Systemic
DNEL	Long term Oral Long term	kg bw/day		Systemic
			population	
		. s	General	Local
	Long term	73.16 mg/	population Workers	Local
DNEL	Inhalation Short term	m ³ 218 mg/m ³	General	Local
DNEL	Short term	292 mg/m³	Workers	Local
DNEL	Long term	100 ppm	Workers	Systemic
DNEL	Long term Oral	33 mg/kg bw/day	General population	Systemic
DNEL	Long term	43.9 mg/m ³	General	Systemic
DNEL	Long term Dermal	78 mg/kg bw/day	General	Systemic
DNEL	Long term Dermal	183 mg/kg	Workers	Systemic
DNEL	Long term	369 mg/m ³	Workers	Systemic
DNEL	Short term	553.5 mg/ m³	Workers	Local
DNEL	Short term	553.5 mg/	Workers	Systemic
DNEL	Long term		Workers	Local
DNEL	Long term Inhalation	3.72 mg/m ³	Workers	Systemic
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	Inhalation DNEL Short term Inhalation DNEL Long term Oral DNEL Long term Oral DNEL Long term Oral DNEL Long term Dermal DNEL Long term Dermal DNEL Long term Dermal DNEL Long term Inhalation DNEL Short term Inhalation DNEL Short term Inhalation DNEL Long term Inhalation DNEL Long term Inhalation DNEL Long term Inhalation DNEL Long term	Inhalation292 mg/m³DNELShort term292 mg/m³Inhalation100 ppmDNELLong term100 ppmInhalation33 mg/kgbw/daybw/dayDNELLong term43.9 mg/m³Inhalation78 mg/kgbw/dayDNELLong term DermalDNELLong term Dermal183 mg/kgbw/dayDNELLong term DermalDNELLong term369 mg/m³Inhalationm³DNELShort term553.5 mg/Inhalationm³DNELShort term553.5 mg/Inhalationm³DNELLong term3.72 mg/m³Inhalation3.72 mg/m³Inhalation3.72 mg/m³	InhalationpopulationDNELShort term292 mg/m³WorkersInhalation100 ppmWorkersDNELLong term100 ppmWorkersInhalation33 mg/kgGeneralDNELLong term Oral33 mg/kgGeneralDNELLong term43.9 mg/m³GeneralInhalation78 mg/kgGeneralDNELLong term Dermal78 mg/kgGeneralDNELLong term Dermal183 mg/kgWorkersDNELLong term Dermal183 mg/kgWorkersDNELLong term369 mg/m³WorkersDNELShort term553.5 mg/MorkersInhalationm³NorkersDNELShort term3.72 mg/m³WorkersInhalation3.72 mg/m³WorkersDNELLong term3.72 mg/m³Workers

	DNEL	Long term Oral	3.95 mg/	General	Systemic
			kg bw/day	population	Systemic
2-dimethylaminoethanol	DNEL	Short term Dermal	$100 \mu\text{g/cm}^2$	Workers	Local
	DNEL	Long term Oral	0.148 mg/	General	Systemic
	DILLE		kg bw/day	population	b yotonno
	DNEL	Long term Dermal	0.25 mg/	Workers	Systemic
	DITE	Long tonin Donnai	kg bw/day	in on one	eyetenne
	DNEL	Long term	0.43755	General	Systemic
		Inhalation	mg/m ³	population	-,
	DNEL	Short term Dermal	1.2 mg/kg	Workers	Systemic
			bw/day		-,
	DNEL	Long term	1.76 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term	1.76 mg/m ³	Workers	Systemic
		Inhalation	J J		-
	DNEL	Short term	5.28 mg/m ³	Workers	Systemic
		Inhalation	_		
	DNEL	Short term	13.53 mg/	Workers	Local
		Inhalation	m³		
3-aminopropyltriethoxysilane	DNEL	Long term Oral	1 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	1 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	2 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term	3.5 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	14 mg/m³	Workers	Systemic
4		Inhalation	0.4	10/	
triethylamine	DNEL	Long term	8.4 mg/m ³	Workers	Local
	DNEL	Inhalation	0.4 ma/m3	Workora	Svotomia
	DNEL	Long term Inhalation	8.4 mg/m ³	Workers	Systemic
	DNEL	Short term	12.6 mg/m ³	Workers	Local
	DINEL	Inhalation	12.0 mg/m	VVUINCIS	LUCAI
	DNEL	Short term	12.6 mg/m ³	Workere	Systemic
	DINEL	Inhalation	12.0 mg/m	VINCIS	Systemic
	DNEL	Long term Dermal	12.1 mg/	Workers	Systemic
		Long tonn Donna	kg bw/day		Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
1-pentanol	Fresh water	0.12 mg/l	-
	Marine water	0.012 mg/l	-
	Secondary Poisoning	1.2 mg/l	-
	Fresh water sediment	0.496 mg/kg	-
	Marine water sediment	0.0496 mg/kg	_
	Sewage Treatment Plant	37 mg/l	-
	Soil	1.068 mg/kg	-
1-methoxy-2-propanol	Marine water	1 mg/l	_
	Fresh water	10 mg/l	-
	Fresh water sediment	52.3 mg/kg	_
	Marine water sediment	5.2 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-
	Soil	4.59 mg/kg	_
Aluminium powder (stabilized)	Fresh water	0.0749 mg/l	-
	Sewage Treatment Plant	20 mg/l	-
2-dimethylaminoethanol	Fresh water	0.066 mg/l	-
•	Marine water	0.007 mg/l	-
	Soil	0.01 mg/kg	-
	Sewage Treatment	10 mg/l	-
e of issue/Date of revision : 4/30/202	4 Date of previous issue	: 4/24/2024	Version : 1.07

		Plant		
8.2 Exposure controls				
Appropriate engineering controls	ach the	ieved by the use of local ex	chaust ventilation antain concentration	practicable, this should be and good general extraction. If as of particulates and solvent ection must be worn.
Individual protection meas	ures			
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.			
Eye/face protection	: Use	safety eyewear designed	to protect against	splash of liquids.
Skin protection				
Hand protection				
combination of chemicals The breakthrough time m The instructions and info replacement must be foll Gloves should be replace	s. nust be g rmation p owed. ed regula	combination of materials th reater than the end use tim rovided by the glove manu rly and if there is any sign c e from defects and that the	e of the product. facturer on use, s of damage to the g	

	these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
ndividual protection meas	<u>res</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
combination of chemicals	erial or combination of materials that will give unlimited resistance to any individual or
	ist be greater than the end use time of the product.
replacement must be follo	nation provided by the glove manufacturer on use, storage, maintenance and wed
	I regularly and if there is any sign of damage to the glove material.
	are free from defects and that they are stored and used correctly.
•	iveness of the glove may be reduced by physical/chemical damage and poor
maintenance. Barrier creams may beln	o protect the exposed areas of the skin but should not be applied once exposure has
occurred.	
Gloves	: Duration / breakthrough time: <1 hour,
	Glove material: NBR, nitrile rubber, material thickness as splash protection: at least
	0.2 mm, (EN374) Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source:
	Expert judgment
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Aluminum.
Odour	:	Not available.
Odour threshold	:	Not available.
Melting point/freezing point	:	Technically not possible to measure
Initial boiling point and	:	100 to 139°C (212 to 282.2°F)
boiling range		
Flammability (solid, gas)		Not available.
Upper/lower flammability or explosive limits	:	Lower: 1.4% Upper: 10%
		Not available.
Flash point	:	Closed cup: 65°C (149°F) [Product does not sustain combustion.]
Auto-ignition temperature		270°C (518°F)
Decomposition temperature	:	Not applicable.
рН	:	7 to 9
Viscosity	:	Not available.
Solubility in water	:	Not available.
Miscible with water	:	Yes.
Partition coefficient: n-octanol/	:	Not applicable.
water		
Vapour pressure		1.8 kPa (13.2 mm Hg) Not available.
Relative density	-	
Density Veneur density		1.02 g/cm ³
Vapour density		Not available.
Explosive properties		Not available.
Oxidising properties		Not available.
Weight volatiles		79.4 % (w/w)
VOC content	-	12.6 % (w/w) (2010/75/EU)

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Further information Not available.

9.2.2 Other safety characteristics

Miscible with water : Yes. Further information Not available.

room temperature (=20°C)

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
	Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1-pentanol	LD50 Dermal	Rabbit - Male	2860 mg/kg	-
	LD50 Oral	Rat	3030 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
2-dimethylaminoethanol	LC50 Inhalation Gas.	Rat	1641 ppm	4 hours
-	LD50 Oral	Rat	2 g/kg	-
3-aminopropyltriethoxysilane	LD50 Dermal	Rabbit	4.29 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-
triethylamine	LD50 Oral	Rat	460 mg/kg	-

Acute toxicity estimates

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	N/A	262737.0	338066.5	195.8	N/A
1-pentanol	3030	2860	N/A	11	N/A
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A
2-dimethylaminoethanol	2000	1100	1641	N/A	N/A
3-aminopropyltriethoxysilane	1570	4290	N/A	N/A	N/A
triethylamine	460	300	N/A	3	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
•	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 3200 mg	-
1-methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-
2-dimethylaminoethanol	Eyes - Oedema of the conjunctivae	Rabbit	3	-	-
	Eyes - Severe irritant	Rabbit	-	5 uL	-
	Skin - Mild irritant	Rabbit	-	445 mg	-
3-aminopropyltriethoxysilane	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
	Skin - Severe irritant	Rabbit	-	ug 24 hours 5 mg	-
triethylamine	Skin - Mild irritant	Rabbit	-	365 mg	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-aminopropyltriethoxysilane	skin	Guinea pig	Sensitising

Mutagenicity

Carcinogenicity

Reproductive toxicity

Teratogenicity

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-pentanol	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects
2-dimethylaminoethanol	Category 3	-	Respiratory tract irritation
triethylamine	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

SECTION 11: Toxicological information

Information on likely routes of exposure	: Not available.	
Potential acute health effects		
Eye contact	: Causes serious eye damage.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the phy-	sical, chemical and toxicological characteristics	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur	

stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

: Adverse symptoms may include the following:

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Ingestion

Product/ingredient name	Result	Species	Exposure
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
		magna	
	Acute LC50 180 ppm Marine water	Fish - Inland silverside -	96 hours
		Menidia beryllina	
	Chronic EC10 0.059 mg/l	Daphnia	21 days
	Chronic NOEC 10 mg/l	Fish	35 days
1-methoxy-2-propanol	Acute LC50 >21100 mg/l	Daphnia - Daphnia	48 hours
, , , , , , , , , , , , , , , , , , ,	Acute LC50 ≥1000 mg/l	Fish - Trout	96 hours
2-dimethylaminoethanol	Acute EC50 98.37 mg/l	Daphnia	48 hours
	Acute LC50 146.63 mg/l Fresh water	Fish	96 hours
ate of issue/Date of revision	: 4/30/2024 Date of previous issue	: 4/24/2024 Version	:1.07 12/

SECTION 12: Ecological information

	logical information		
triethylamine	Acute LC50 24 mg/l	Fish	96 hours
	Acute NOEC 1.1 mg/l	Algae	72 hours
	Acute NOEC 12 mg/l Fresh water	Daphnia	48 hours

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1-pentanol	OECD 310 Ready Biodegradability - CO2 in Sealed Vessels (Headspace Test)	100 % - Readily - 18 days	-	-
1-methoxy-2-propanol 2-dimethylaminoethanol	OECD 301E OECD 302C Inherent Biodegradability: Modified MITI Test (II)	96 % - 28 days 60.5 % - Readily - 28 days	-	-
triethylamine	OECD 301B Ready Biodegradability - CO2 Evolution Test	80.3 % - Readily - 29 days	-	-
Conclusion/Summary	: Not available.		•	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-pentanol	-	-	Readily
1-methoxy-2-propanol	-	-	Readily
2-dimethylaminoethanol	-	-	Readily
triethylamine	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1-pentanol	1.51	-	Low
1-methoxy-2-propanol	<1	-	Low
2-dimethylaminoethanol	-0.55	-	Low
3-aminopropyltriethoxysilane	1.7	3.4	Low
triethylamine	1.45	<0.5	Low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: The classif	: The classification of the product may meet the criteria for a hazardous waste.	
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging		Waste catalogue	
	15 01 10*	packaging containing residues of or contaminated by	

		hazardous substances
S	pecial precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9003	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (1-pentanol, 1-methoxy-2-propanol)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 SYROX TINT COARSE SILVER

SECTION 14: Transport information

14.7 Transport in bulk: Not available.according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions	Not applicable.
on the manufacture,	
placing on the market	
and use of certain	
dangerous substances,	
mixtures and articles	

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

	ſ	Product/ingredient name	List name	Name on list	Classification	Notes
--	---	-------------------------	-----------	--------------	----------------	-------

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

15.2 Chemical safety : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
Procedure used to derive th	vPvB = Very Persistent and Very Bioaccumulative
Procedure lised to derive ti	

Procedure used to derive the classification

SECTION 16: Other information

Classification	Justification	
Eye Dam. 1, H318 Aquatic Chronic 3, H412	Calculation method Calculation method	

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 1	FLAMMABLE SOLIDS - Category 1
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 4/30/2024
revision	
Version	: 1.07

Date of previous issue : 4/24/2024

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

Date of issue/Date of revision	: 4/30/2024	Date of previous issue	: 4/24/2024	Version : 1.07	16/17
--------------------------------	-------------	------------------------	-------------	----------------	-------

SECTION 16: Other information