

## SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product identifier	: S708
Product name	: SYROX TINT FINE GREEN PEARL
Product type	: Liquid.
Other means of identification	: 1250088668
Date of issue	: 29 February 2024
Version	: 1.05
Date of previous issue	: 29 December 2023
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Identified uses	: Coating component.
Uses advised against	: Not for sale to or use by consumers.
1.3 Details of the supplier of	the safety data sheet
Axalta Coating Systems Ger Christbusch 25 DE 42285 Wuppertal +49 (0)202 529-0	many GmbH & Co. KG
e-mail address of person responsible for this SDS	: sds-competence@axalta.com
1.4 Emergency telephone nu	umber
<u>Supplier</u>	

oupplier	
Telephone number	: +(44)-870-8200418
Hours of operation	:

## **SECTION 2: Hazards identification**

2.1 Classification of the sub	ostance or mixture
Product definition	: Mixture
Classification according to Eye Dam. 1, H318 Aquatic Chronic 3, H412	<u>o UK CLP/GHS</u>
The product is classified as	hazardous according to UK CLP Regulation SI 2019/720 as amended.
Ingredients of unknown toxicity	<ul> <li>1 percent of the mixture consists of component(s) of unknown acute oral toxicity</li> <li>1.1 percent of the mixture consists of component(s) of unknown acute dermal toxicity</li> <li>1.1 percent of the mixture consists of component(s) of unknown acute inhalation toxicity</li> </ul>
Ingredients of unknown ecotoxicity	: Contains 1.1% of components with unknown hazards to the aquatic environment
See Section 16 for the full te	ext of the H statements declared above.
See Section 11 for more det	tailed information on health effects and symptoms.

Date of issue/Date of revision	: 2/29/2024	Date of previous issue	: 12/29/2023	Version	:1.05	1/15
--------------------------------	-------------	------------------------	--------------	---------	-------	------

## **SECTION 2: Hazards identification**

2.2 Label elements Hazard pictograms	:	
Signal word	:	Danger
Contains	:	1-pentanol
Hazard statements	:	₩318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	280 - Wear eye or face protection. P273 - Avoid release to the environment.
Response	:	P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	₱501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

## **SECTION 3:** Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
<mark>≇-</mark> pentanol	REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1	<10	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1] [2]

## **SECTION 3: Composition/information on ingredients**

		ingreatents		
triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8	≤0.2	STOT SE 3, H335 Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 See Section 16 for the full text of the H statements declared	[1] [2]
			above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Туре

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains  $\ge 1\%$  of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

## **SECTION 4: First aid measures**

#### Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

## **SECTION 5: Firefighting measures**

-		
5.1 Extinguishing media Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray.
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising fi	rom	the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

# **Special protective** : Appropriate breathing apparatus may be required. equipment for fire-fighters

## SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

Date of issue/Date of revision	: 2/29/2024	Date of previous issue	: 12/29/2023	Version : 1.05	4/15
--------------------------------	-------------	------------------------	--------------	----------------	------

## **SECTION 6: Accidental release measures**

6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information
sections	See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values	Exposure limit values				
1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m <sup>3</sup> 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m <sup>3</sup> 8 hours.					
2-dimethylaminoethanol	TWA: 100 ppm 8 hours. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 22 mg/m <sup>3</sup> 15 minutes. STEL: 6 ppm 15 minutes. TWA: 2 ppm 8 hours.					
Date of issue/Date of revision : 2/29/20	TWA: 7.4 mg/m³ 8 hours.           24         Date of previous issue         : 12/29/2023         Version         : 1.05	5/15				

## **SECTION 8: Exposure controls/personal protection**

triethylamine	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 17 mg/m <sup>3</sup> 15 minutes. TWA: 2 ppm 8 hours. TWA: 8 mg/m <sup>3</sup> 8 hours. STEL: 4 ppm 15 minutes.

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring	: Reference should be made to appropriate monitoring standards. Reference to	
procedures	national guidance documents for methods for the determination of hazardous	
-	substances will also be required.	

#### **DNELs/DMELs**

Туре	Exposure	Value	Population	Effects
DNEL	Long term Inhalation	20 ppm	Workers	Systemic
DNEL	Long term Oral	12.5 mg/	General	Systemic
DNEL		13 mg/m <sup>s</sup>		Local
		73 16 mg/		Local
DNEL		-	VUINEIS	LUCAI
			General	Local
DINCE		210 mg/m		Local
DNFI		292 mg/m <sup>3</sup>		Local
DITLE		202 mg/m		Loodi
DNEL		100 ppm	Workers	Systemic
DITE		roo ppin		eyeterme
DNEL		33 ma/ka	General	Systemic
	5			,
DNEL	Long term			Systemic
	Inhalation	Ū		,
DNEL	Long term Dermal	78 mg/kg	General	Systemic
	U U	bw/day	population	-
DNEL	Long term Dermal	183 mg/kg	Workers	Systemic
		bw/day		
DNEL	Long term	369 mg/m <sup>3</sup>	Workers	Systemic
		/		
DNEL			Workers	Local
DUE				
DNEL			Workers	Systemic
			Workoro	Local
				Systemic
DINLL	Long term Oral	•		Systemic
	Long term Dermal			Systemic
DINCE	Long term Derma		Workers	Gysternie
DNEI	Long term		General	Systemic
DITLE				Cyclonnic
DNEL				Systemic
				,
DNEL	Long term	1.76 mg/m <sup>3</sup>	Workers	Local
	Inhalation			
DNEL	Long term	1.76 mg/m <sup>3</sup>	Workers	Systemic
	Inhalation			
DNEL	Short term	5.28 mg/m <sup>3</sup>	Workers	Systemic
	Inhalation			
DNEL		•	Workers	Local
<b></b>				
DNEL		8.4 mg/m <sup>3</sup>	Workers	Local
<b></b>				
DNEL	Long term	8.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	DNELLong term InhalationDNELLong term OralDNELLong term InhalationDNELLong term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term OralDNELLong term DermalDNELLong term DermalDNELLong term DermalDNELLong term DermalDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term Dermal InhalationDNELLong term OralDNELLong term Dermal InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELShort term DermalDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term 	DNELLong term Inhalation20 ppmDNELLong term Oral12.5 mg/ kg bw/dayDNELLong term Oral13 mg/m³DNELLong term73.16 mg/ InhalationDNELShort term218 mg/m³DNELShort term292 mg/m³InhalationDNELShort termDNELShort term292 mg/m³InhalationInhalationDNELLong term100 ppmInhalationNELLong term OralDNELLong term Oral33 mg/kgbw/dayDNELLong term DermalDNELLong term Dermal78 mg/kgbw/dayDNELLong term DermalDNELLong term Dermal183 mg/kgbw/dayDNELLong term DermalDNELShort term553.5 mg/Inhalationm³DNELShort term Dermal100 µg/cm²DNELLong term Dermal0.025 mg/MELLong term Dermal0.025 mg/MELLong term Dermal0.25 mg/NELShort term Dermal1.2 mg/kgbw/dayDNELLong term1.76 mg/m³DNELLong term1.76 mg/m³DNELLong term1.76 mg/m³InhalationDNELShort termDNELShort term5.28 mg/m³InhalationM³DNELShort term13.53 mg/InhalationM³DNELShort term5.28 mg/m³InhalationM³ <td< td=""><td>DNELLong term Inhalation20 ppmWorkersDNELLong term Oral12.5 mg/ kg bw/dayGeneral populationDNELLong term Inhalation13 mg/m³General populationDNELLong term Inhalation73.16 mg/ m³WorkersDNELLong term Inhalation292 mg/m³General populationDNELShort term Inhalation292 mg/m³General populationDNELShort term Inhalation292 mg/m³General populationDNELLong term Oral Inhalation33 mg/kg bw/dayGeneral populationDNELLong term Oral Inhalation33 mg/kg bw/dayGeneral populationDNELLong term Dermal78 mg/kg bw/dayGeneral populationDNELLong term Dermal183 mg/kg bw/dayWorkersDNELLong term Dermal183 mg/kg bw/dayWorkersDNELLong term Dermal100 µg/cm² NELWorkersDNELShort term population553.5 mg/ m³WorkersDNELShort term Dermal100 µg/cm² NGW/dayWorkersDNELLong term Oral0.25 mg/ workersWorkersDNELLong term Dermal1.76 mg/m³ mg/m³WorkersDNELLong term Inhalation1.76 mg/m³ WorkersWorkersDNELLong term Inhalation1.76 mg/m³ WorkersWorkersDNELShort term Inhalation5.28 mg/m³ WorkersWorkersDNELShort term<b< td=""></b<></td></td<>	DNELLong term Inhalation20 ppmWorkersDNELLong term Oral12.5 mg/ kg bw/dayGeneral populationDNELLong term Inhalation13 mg/m³General populationDNELLong term Inhalation73.16 mg/ m³WorkersDNELLong term Inhalation292 mg/m³General populationDNELShort term Inhalation292 mg/m³General populationDNELShort term Inhalation292 mg/m³General populationDNELLong term Oral Inhalation33 mg/kg bw/dayGeneral populationDNELLong term Oral Inhalation33 mg/kg bw/dayGeneral populationDNELLong term Dermal78 mg/kg bw/dayGeneral populationDNELLong term Dermal183 mg/kg bw/dayWorkersDNELLong term Dermal183 mg/kg bw/dayWorkersDNELLong term Dermal100 µg/cm² NELWorkersDNELShort term population553.5 mg/ m³WorkersDNELShort term Dermal100 µg/cm² NGW/dayWorkersDNELLong term Oral0.25 mg/ workersWorkersDNELLong term Dermal1.76 mg/m³ mg/m³WorkersDNELLong term Inhalation1.76 mg/m³ WorkersWorkersDNELLong term Inhalation1.76 mg/m³ WorkersWorkersDNELShort term Inhalation5.28 mg/m³ WorkersWorkersDNELShort term <b< td=""></b<>

## **SECTION 8: Exposure controls/personal protection**

	13/P		Clion		
		Inhalation			
DN	<b>IEL</b>	Short term	12.6 mg/m <sup>3</sup>	Workers	Local
		Inhalation	-		
DN	<b>IEL</b>	Short term	12.6 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	-		-
DN	NEL	Long term Dermal	12.1 mg/	Workers	Systemic
		-	kg bw/day		-

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
<mark>⊁</mark> -pentanol	Fresh water	0.12 mg/l	-
	Marine water	0.012 mg/l	-
	Secondary Poisoning	1.2 mg/l	-
	Fresh water sediment	0.496 mg/kg	-
	Marine water sediment	0.0496 mg/kg	-
	Sewage Treatment	37 mg/l	-
	Plant	0	
	Soil	1.068 mg/kg	-
1-methoxy-2-propanol	Marine water	1 mg/l	-
	Fresh water	10 mg/l	-
	Fresh water sediment	52.3 mg/kg	-
	Marine water sediment	5.2 mg/kg	-
	Sewage Treatment	100 mg/l	-
	Plant	-	
	Soil	4.59 mg/kg	-
2-dimethylaminoethanol	Fresh water	0.066 mg/l	-
-	Marine water	0.007 mg/l	-
	Soil	0.01 mg/kg	-
	Sewage Treatment	10 mg/l	-
	Plant	-	

#### 8.2 Exposure controls

8.2 Exposure controls	
Appropriate engineering controls	: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
Individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
combination of chemicals. The breakthrough time mu The instructions and inforr replacement must be follo Gloves should be replaced Always ensure that gloves	erial or combination of materials that will give unlimited resistance to any individual or ast be greater than the end use time of the product. nation provided by the glove manufacturer on use, storage, maintenance and wed. I regularly and if there is any sign of damage to the glove material. are free from defects and that they are stored and used correctly. iveness of the glove may be reduced by physical/chemical damage and poor

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves	<ul> <li>Duration / breakthrough time: &lt;1 hour, Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374) Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)</li> </ul>
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source:
	Expert judgment
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Green.
Odour	:	Not available.
Odour threshold	:	Not available.
Melting point/freezing point	:	Technically not possible to measure
Initial boiling point and boiling range	:	100 to 139°C (212 to 282.2°F)
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Lower: 1.4% Upper: 10%
Flash point	:	Closed cup: 60°C (140°F) [Product does not sustain combustion.]
Auto-ignition temperature	:	270°C (518°F)
Decomposition temperature	:	Not applicable.
рН	:	7.5 to 8
Viscosity	:	Dynamic: 141 mPa·s Kinematic: 134 mm²/s
Solubility in water	:	Not available.
Miscible with water	:	Yes.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	:	1.8 kPa (13.2 mm Hg)
Relative density	:	Not available.
Density	:	1.053 g/cm³

Date of issue/Date of revision

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 SYROX TINT FINE GREEN PEARL

## **SECTION 9: Physical and chemical properties**

-	
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Weight volatiles	: 78.2 % (w/w)
VOC content	: 10.1 % (w/w)

(2010/75/EU)

room temperature (=20°C)

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.		
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.		
10.6 Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.		
	Not applicable		

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<mark>1∕-</mark> pentanol	LD50 Dermal	Rabbit - Male	2860 mg/kg	-
·	LD50 Oral	Rat	3030 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
2-dimethylaminoethanol	LC50 Inhalation Gas.	Rat	1641 ppm	4 hours
-	LD50 Oral	Rat	2 g/kg	-
triethylamine	LD50 Oral	Rat	460 mg/kg	-

## **SECTION 11: Toxicological information**

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	N/A	295655.1	396980.4	191.4	N/A
1-pentanol	3030	2860	N/A	11	N/A
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A
2-dimethylaminoethanol	2000	1100	1641	N/A	N/A
triethylamine	460	300	N/A	3	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
	Skin - Severe irritant	Rabbit	-	mg 24 hours 3200 mg	-
1-methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-
2-dimethylaminoethanol	Eyes - Oedema of the conjunctivae	Rabbit	3	-	-
	Eyes - Severe irritant	Rabbit	-	5 uL	-
	Skin - Mild irritant	Rabbit	-	445 mg	-
triethylamine	Skin - Mild irritant	Rabbit	-	365 mg	-

#### **Sensitisation**

#### Mutagenicity

#### **Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

#### **Reproductive toxicity**

#### **Teratogenicity**

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
✓-pentanol	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects
2-dimethylaminoethanol	Category 3	-	Respiratory tract irritation
triethylamine	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

#### Information on likely routes : Not available.

#### of exposure Potential acute health effects

Potential acute nearth effects	
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards
Skin contact	: No known significant effects or critical hazards
Ingestion	: No known significant effects or critical hazards

Date of issue/Date of revision

## **SECTION 11: Toxicological information**

Symptoms related to the	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Delayed and immediate e	ffects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information

: Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
✓pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
		magna	
	Acute LC50 180 ppm Marine water	Fish - Inland silverside -	96 hours
		Menidia beryllina	
	Chronic EC10 0.059 mg/l	Daphnia	21 days
	Chronic NOEC 10 mg/l	Fish	35 days
1-methoxy-2-propanol	Acute LC50 >21100 mg/l	Daphnia - Daphnia	48 hours
	Acute LC50 ≥1000 mg/l	Fish - Trout	96 hours
2-dimethylaminoethanol	Acute EC50 98.37 mg/l	Daphnia	48 hours
-	Acute LC50 146.63 mg/l Fresh water	Fish	96 hours
triethylamine	Acute LC50 24 mg/l	Fish	96 hours
-	Acute NOEC 1.1 mg/l	Algae	72 hours
	Acute NOEC 12 mg/l Fresh water	Daphnia	48 hours

Conclusion/Summary

: Not available.

#### 12.2 Persistence and degradability

## **SECTION 12: Ecological information**

Product/ingredient name	Test	Result	Dose	Inoculum
<b>1∕</b> -pentanol	OECD 310	100 % - Readily - 18 days	-	-
	Ready			
	Biodegradability -			
	CO2 in Sealed			
	Vessels			
	(Headspace			
	Test)			
1-methoxy-2-propanol	OECD 301E	96 % - 28 days	-	-
2-dimethylaminoethanol	OECD 302C	60.5 % - Readily - 28 days	-	-
	Inherent			
	Biodegradability:			
	Modified MITI			
	Test (II)			
triethylamine	OECD 301B	80.3 % - Readily - 29 days	-	-
	Ready			
	Biodegradability -			
	CO2 Evolution			
	Test			

#### **Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
✓pentanol	-	-	Readily
1-methoxy-2-propanol	-	-	Readily
2-dimethylaminoethanol	-	-	Readily
triethylamine	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
✓pentanol	1.51	-	Low
1-methoxy-2-propanol	<1	-	Low
2-dimethylaminoethanol	-0.55	-	Low
triethylamine	1.45	<0.5	Low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Other adverse effects : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### Product Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. /15

Date of issue/Date of revision	: 2/29/2024	Date of previous issue	: 12/29/2023	Version : 1.05	12/1
--------------------------------	-------------	------------------------	--------------	----------------	------

## **SECTION 13: Disposal considerations**

	•				
	lazardous waste	: The classification	: The classification of the product may meet the criteria for a hazardous waste.		
<u>P</u> a	ackaging				
I	Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.			
	Type of packaging		Waste catalogue		
		15 01 10*	packaging containing residues of or contaminated by		

	hazardous substances
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

ADR/RID	ADN	IMDG	IATA		
Not regulated.	<b>9</b> 006	Not regulated.	Not regulated.		
-	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-		
-	<b>9</b>	-	-		
-	-	-	-		
No.	¥es.	No.	No.		
	Not regulated	Not regulated.       9006         -       ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.         -       97         -       97	Not regulated.       9006       Not regulated.         -       ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.       -         -       97       -         -       97       -         -       97       -		

## Additional information

ADN

- : The product is only regulated as a dangerous good when transported in tank vessels.
- **14.6 Special precautions for : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# 14.7 Transport in bulk: Not available.according to IMOinstruments

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### <u>UK (GB)/REACH</u>

#### Annex XIV - List of substances subject to authorisation

#### <u>Annex XIV</u>

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

## **SECTION 15: Regulatory information**

Annex XVII - RestrictionsNot applicable.on the manufacture,placing on the marketand use of certain

#### dangerous substances,

mixtures and articles

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### National regulations

Product/ingredient name	List name	Name on list	Classification	Notes	

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

15.2 Chemical safety	:	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration BRN = REACH Registration Number</li> </ul>
	RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Classification	Justification	
	Calculation method	
Aquatic Chronic 3, H412	Calculation method	

#### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

## **SECTION 16: Other information**

H412 Harmful to aquatic life with long lasting effects.

#### Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 2/29/2024
Date of issue/ Date of	: 2/29/2024
revision	
Date of previous issue	e : 12/29/2023
Version	: 1.05

#### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.