

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier					
Product identifier	: S712				
Product name	: SYROX TINT FINE WHITE PEARL				
Product type	: Liquid.				
Other means of identification	: 1250088672				
Date of issue	: 28 February 2024				
Version	: 1.05				
Date of previous issue	: 1 February 2024				
1.2 Relevant identified uses	s of the substance or mixture and uses advised against				
Identified uses	: Coating component.				
Uses advised against	: Not for sale to or use by consumers.				
1.3 Details of the supplier o	f the safety data sheet				
Axalta Coating Systems Ger Christbusch 25 DE 42285 Wuppertal +49 (0)202 529-0	many GmbH & Co. KG				
e-mail address of person responsible for this SDS	: sds-competence@axalta.com				
1.4 Emergency telephone n	umber				
<u>Supplier</u>					
Telephone number	: +(44)-870-8200418				
Hours of operation	:				

SECTION 2: Hazards identification

2.1 Classification of the sub	sta	nce or mixtı	ure				
Product definition	:	Mixture					
<u>Classification according to</u> Eye Dam. 1, H318 Aquatic Chronic 3, H412	UK	<u>(CLP/GHS</u>					
The product is classified as h	naza	ardous accor	ding to UK CLP Regula	ation SI 2019/720 as a	mended.		
Ingredients of unknown toxicity	:	1.1 percent toxicity	t of the mixture consists t of the mixture consists t of the mixture consists	s of component(s) of u	nknown acute d	ermal	-
Ingredients of unknown ecotoxicity	:	Contains 1.	.1% of components wit	h unknown hazards to	the aquatic envi	ironment	t
See Section 16 for the full te	xt oʻ	f the H stater	ments declared above.				
See Section 11 for more deta	aileo	d information	on health effects and	symptoms.			
Date of issue/Date of revision		: 2/28/2024	Date of previous issue	: 2/1/2024	Version	:1.05	1/16

SECTION 2: Hazards identification

2.2 Label elements Hazard pictograms	:	
Signal word	:	Danger
Contains	:	1-pentanol
Hazard statements	:	H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	P280 - Wear eye or face protection. P273 - Avoid release to the environment.
Response	:	P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
1-pentanol	REACH #: 01-2119491284-34 EC: 200-752-1 CAS: 71-41-0 Index: 603-200-00-1	<10	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
2-dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	<1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1] [2]

SECTION 3: Composition/information on ingredients

01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Acute Tox. 3, H311 Skin Corr. 1A, H314 Eye Dam. 1, H318			ingreatente		
STOT SE 3, H335 See Section 16 for the full text of the H statements declared above.	triethylamine	01-2119475467-26 EC: 204-469-4	≤0.2	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 See Section 16 for the full text of the H statements declared	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains $\ge 1\%$ of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

SECTION 4: First aid measures

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising fi	rom	the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective : Appropriate breathing apparatus may be required. equipment for fire-fighters

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

Date of issue/Date of revision	: 2/28/2024	Date of previous issue	: 2/1/2024	Version : 1.05 4/16
--------------------------------	-------------	------------------------	------------	---------------------

SECTION 6: Accidental release measures

6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information
sections	See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values			
1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes.			
	STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.			
2-dimethylaminoethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 22 mg/m ³ 15 minutes. STEL: 6 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 7.4 mg/m ³ 8 hours.			
hate of issue/Date of revision : 2/28/2024	Date of previous issue : 2/1/2024 Version : 1.05 5/16			

SECTION 8: Exposure controls/personal protection

triethylamine	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 17 mg/m ³ 15 minutes. TWA: 2 ppm 8 hours. TWA: 8 mg/m ³ 8 hours. STEL: 4 ppm 15 minutes.

Biological exposure indices

No exposure indices known.

Recommended monitoring	:	Reference should be made to appropriate monitoring standards. Reference to
procedures		national guidance documents for methods for the determination of hazardous
-		substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1-pentanol	DNEL	Long term Inhalation	20 ppm	Workers	Systemic
	DNEL	Long term Oral	12.5 mg/	General	Systemic
			kg bw/day	population	-)
	DNEL	Long term	13 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	73.16 mg/	Workers	Local
		Inhalation	m ³		
	DNEL	Short term	218 mg/m ³	General	Local
	DITEE	Inhalation	210 mg/m	population	Loodi
	DNEL	Short term	292 mg/m ³	Workers	Local
	DITEE	Inhalation	202 mg/m	T officio	Loodi
1-methoxy-2-propanol	DNEL	Long term	100 ppm	Workers	Systemic
	DINCE	Inhalation	roo ppin	Wonters	Cysternio
	DNEL	Long term Oral	33 mg/kg	General	Systemic
			bw/day	population	5,000,000
	DNEL	Long term	43.9 mg/m ³	General	Systemic
		Inhalation		population	5,000,000
	DNEL	Long term Dermal	78 mg/kg	General	Systemic
		Long torm Derma	bw/day	population	
	DNEL	Long term Dermal	183 mg/kg	Workers	Systemic
	DINCL	Long term Derma	bw/day	Workers	Oysternie
	DNEL	Long term	369 mg/m ³	Workers	Systemic
	DINCL	Inhalation	505 mg/m	Workers	Oysternie
	DNEL	Short term	553.5 mg/	Workers	Local
	DINCL	Inhalation	m ³	WOIKEIS	Local
	DNEL	Short term	553.5 mg/	Workers	Systemic
	DINCL	Inhalation	m ³	Workers	Oysternie
2-dimethylaminoethanol	DNEL	Short term Dermal	100 µg/cm ²	Workers	Local
	DNEL	Long term Oral	0.148 mg/	General	Systemic
	DINCE	Long term oral	kg bw/day	population	Cysternie
	DNEL	Long term Dermal	0.25 mg/	Workers	Systemic
	DINCL	Long term Derma	kg bw/day	Workers	Oysternie
	DNEL	Long term	0.43755	General	Systemic
		Inhalation	mg/m ³	population	Gysternic
	DNEL	Short term Dermal	1.2 mg/kg	Workers	Systemic
			bw/day		- July Stormo
	DNEL	Long term	1.76 mg/m ³	Workers	Local
		Inhalation	1.70 mg/m		
	DNEL	Long term	1.76 mg/m ³	Workers	Systemic
		Inhalation	1.70 mg/m		- July Stormo
	DNEL	Short term	5.28 mg/m ³	Workers	Systemic
		Inhalation	5.20 mg/m	VV UINCIS	Gysternic
	DNEL	Short term	13.53 mg/	Workers	Local
		Inhalation	m ³	VV UINCIS	LUCAI
triethylamine	DNEL	Long term	8.4 mg/m ³	Workers	Local
arcarylannine		Inhalation	0.4 mg/m	VV UINCIS	LUCAI
	DNEL	Long term	8.4 mg/m ³	Workers	Systemic
	DINEL		0.4 mg/m	VVUINCIS	Systemic
	28/2024		: 2/1/202		/ersion : 1.05

SECTION 8: Exposure controls/personal protection

		Inhalation	10.0	M/ and a na	Land
	DNEL	Short term Inhalation	12.6 mg/m ³	vvorkers	Local
	DNEL	Short term Inhalation	12.6 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	0	Workers	Systemic
			kg bw/day		

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
1-pentanol	Fresh water	0.12 mg/l	-
	Marine water	0.012 mg/l	-
	Secondary Poisoning	1.2 mg/l	-
	Fresh water sediment	0.496 mg/kg	-
	Marine water sediment	0.0496 mg/kg	-
	Sewage Treatment	37 mg/l	-
	Plant	5	
	Soil	1.068 mg/kg	-
1-methoxy-2-propanol	Marine water	1 mg/l	-
	Fresh water	10 mg/l	-
	Fresh water sediment	52.3 mg/kg	-
	Marine water sediment	5.2 mg/kg	-
	Sewage Treatment	100 mg/l	-
	Plant	0	
	Soil	4.59 mg/kg	-
2-dimethylaminoethanol	Fresh water	0.066 mg/l	-
5	Marine water	0.007 mg/l	-
	Soil	0.01 mg/kg	-
	Sewage Treatment	10 mg/l	-
	Plant	U U	

8.2 Exposure controls

o.z Exposure controis	
Appropriate engineering controls	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
Individual protection meas	sures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
combination of chemical The breakthrough time n The instructions and info replacement must be fol Gloves should be replac Always ensure that glove	nust be greater than the end use time of the product. Irmation provided by the glove manufacturer on use, storage, maintenance and

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

SECTION 8: Exposure controls/personal protection

Gloves	 Duration / breakthrough time: <1 hour, Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374) Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source:
	Expert judgment
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: Liquid.	
Colour	: White.	
Odour	: Not available.	
Odour threshold	: Not available.	
Melting point/freezing point	: Technically not possible to measure	
Initial boiling point and boiling range	: 100 to 139°C (212 to 282.2°F)	
Flammability (solid, gas)	: Not available.	
Upper/lower flammability or explosive limits	: Lower: 1.4% Upper: 10%	
Flash point	: Closed cup: 60°C (140°F) [Product does not sustain combustion.]	
Auto-ignition temperature	: 270°C (518°F)	
Decomposition temperature	: Not applicable.	
рН	: 7.5 to 8	
Viscosity	: Dynamic: 141 mPa·s Kinematic: 134 mm²/s	
Solubility(ies)	:	
Media	Result	
cold water	Soluble	
Solubility in water	: Not available.	
Miscible with water	: Yes.	

SECTION 9: Physical and chemical properties

- -		
Partition coefficient: n-octar water	10l/ : Not applicable.	
Vapour pressure	: 1.8 kPa (13.2 mm Hg)	
Relative density	: Not available.	
Density	: 1.051 g/cm³	
Vapour density	: Not available.	
Explosive properties	: Not available.	
Oxidising properties	: Not available.	
Weight volatiles	: 78.2 % (w/w)	
VOC content	: 10.1 % (w/w)	(2010/75/EU)

room temperature (=20°C)

SECTION 10: Stability and reactivity					
10.1 Reactivity	Io specific test data related to reactivity available for this product or its ingredie	ents.			
10.2 Chemical stability	Stable under recommended storage and handling conditions (see Section 7).				
10.3 Possibility of hazardous reactions	Inder normal conditions of storage and use, hazardous reactions will not occu	ır.			
10.4 Conditions to avoid	Vhen exposed to high temperatures may produce hazardous decomposition products.				
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions exiting agents, strong alkalis, strong acids.	:			
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide arbon dioxide, smoke, oxides of nitrogen.	? ,			
	lot applicable				

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
1-pentanol	LD50 Dermal	Rabbit - Male	2860 mg/kg	-
	LD50 Oral	Rat	3030 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
2-dimethylaminoethanol	LC50 Inhalation Gas.	Rat	1641 ppm	4 hours
	LD50 Oral	Rat	2 g/kg	-
triethylamine	LD50 Oral	Rat	460 mg/kg	-

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	N/A	295655.1	397220.7	191.4	N/A
1-pentanol	3030	2860	N/A	11	N/A
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A
2-dimethylaminoethanol	2000	1100	1641	N/A	N/A
triethylamine	460	300	N/A	3	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
	Skin - Severe irritant	Rabbit	-	mg 24 hours 3200 mg	-
1-methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-
2-dimethylaminoethanol	Eyes - Oedema of the conjunctivae	Rabbit	3	-	-
	Eyes - Severe irritant	Rabbit	-	5 uL	-
	Skin - Mild irritant	Rabbit	-	445 mg	-
triethylamine	Skin - Mild irritant	Rabbit	-	365 mg	-

Sensitisation

Mutagenicity

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Reproductive toxicity

Teratogenicity

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-pentanol	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects
2-dimethylaminoethanol	Category 3	-	Respiratory tract irritation
triethylamine	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

SECTION 11: Toxicological information

Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
		magna	
	Acute LC50 180 ppm Marine water	Fish - Inland silverside -	96 hours
		Menidia beryllina	
	Chronic EC10 0.059 mg/l	Daphnia	21 days
	Chronic NOEC 10 mg/l	Fish	35 days
1-methoxy-2-propanol	Acute LC50 >21100 mg/l	Daphnia - Daphnia	48 hours
2	Acute LC50 ≥1000 mg/l	Fish - Trout	96 hours
2-dimethylaminoethanol	Acute EC50 98.37 mg/l	Daphnia	48 hours
-	Acute LC50 146.63 mg/l Fresh water	Fish	96 hours
ate of issue/Date of revision	: 2/28/2024 Date of previous issue	: 2/1/2024 Version	:1.05 11/

SECTION 12: Ecological information

	logioal information		
triethylamine	Acute LC50 24 mg/l	Fish	96 hours
	Acute NOEC 1.1 mg/l	Algae	72 hours
	Acute NOEC 12 mg/l Fresh water	Daphnia	48 hours

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1-pentanol	OECD 310 Ready Biodegradability - CO2 in Sealed Vessels (Headspace Test)	100 % - Readily - 18 days	-	-
1-methoxy-2-propanol 2-dimethylaminoethanol	OECD 301E OECD 302C Inherent Biodegradability: Modified MITI Test (II)	96 % - 28 days 60.5 % - Readily - 28 days	-	-
triethylamine	OECD 301B Ready Biodegradability - CO2 Evolution Test	80.3 % - Readily - 29 days	-	-
Conclusion/Summary	: Not available.		•	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability		
1-pentanol	-	-	Readily		
1-methoxy-2-propanol	-	-	Readily		
2-dimethylaminoethanol	-	-	Readily		
triethylamine	-	-	Readily		

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1-pentanol	1.51	-	Low
1-methoxy-2-propanol	<1	-	Low
2-dimethylaminoethanol	-0.55	-	Low
triethylamine	1.45	<0.5	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Waste catalogue

Waste code	Waste designation
08 01 19*	aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue		
	15 01 10*	packaging containing residues of or contaminated by hazardous substances	
Special precautions	This material and its container must be disposed of in a safe way. Care taken when handling emptied containers that have not been cleaned or r Empty containers or liners may retain some product residues. Avoid disp spilt material and runoff and contact with soil, waterways, drains and sew		

SECTION 14: Transport information

	-			
	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision

SECTION 14: Transport information

14.7 Transport in bulk : Not available. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB)/REACH</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Not applicable.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

15.2 Chemical safety	:	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

SECTION 16: Other information

Classification	Justification		
Eye Dam. 1, H318 Aquatic Chronic 3, H412	Calculation method Calculation method		

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Full text of classifications

Date of issue/ Date of	: 2/28/2024
Date of printing	: 2/28/2024
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Acute Tox. 4	ACUTE TOXICITY - Category 4
Acute Tox. 3	ACUTE TOXICITY - Category 3

revision		
Date of previous issue	:	2/1/2024
Version	:	1.05

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

SECTION 16: Other information