

### TECHNICAL DATA SHEET

### ESS 06-08-10 – Finixa easy seam sealer on a roll

OEM profile.

Can be applied quickly and easily.

Heat resistant and can be overpainted immediately.

	<b>Width</b>	<b>Thickness</b>	<b>Length</b>
ESS 06	6 mm	1.84 mm	9 m
ESS 08	8 mm	1.87 mm	9 m
ESS 10	10 mm	1.90 mm	9 m

#### Rubber characteristic

Specific gravity 1.35

Tensile strength 2,1

#### Coating adhesion characteristics

Lacquer paint Excellent

Urethane paint Excellent

Waterbased paint Good

#### Application

- Ensure the area is smooth and free of grease and oil;
- Use a heat gun to ensure the application temperature is above 25°C;
- Apply a fine coat of adhesion promotor (TSP 030) to the bare metal;
- Apply the tape, pressing it firmly into place. Use the roller ESS 20;
- Do not stretch the tape during application;
- Very tight corners may need two small notches of sealant along the inner corner or cut the tape 1 cm from the corner and finish with sealant;
- Apply the wet sealant to the ends;
- Easy Seam Sealer is heat resistant and can be overpainted immediately.

#### Shelf life

2 years



**NEW SIZE!**

**ESS 06**

**6mm x 9m**

For Japanese, Korean, Citroën  
and Peugeot cars



**ESS 08**

**8mm x 9m**

80% of the German market  
(Mercedes, Volkswagen, Audi)



**ESS 10**

**10mm x 9m**

BMW, vans and large SUVs

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.*

**Chemicar Europe nv**  
Baarbeek 2  
2070 Zwijndrecht  
België-Belgium

T.: +32 3 234 87 80  
F.: +32 3 234 87 89  
info@chemicar.eu  
www.chemicar.eu

*Chemical Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.*

---

**Chemical Europe nv**  
Baarbeek 2  
2070 Zwijndrecht  
België-Belgium

T.: +32 3 234 87 80  
F.: +32 3 234 87 89  
info@chemical.eu  
www.chemical.eu